



Part Number:	SP520104-1	
Description:	DRAWN	11/9/2018
	CJ	
Dynamic Speaker	CHECKED	11/9/2018
	C.H.	
	APPROVED	11/9/2018
	C.E.	
This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at <a href="http://www.dbunlimitedco.com">www.dbunlimitedco.com</a>		


Top View



Side View



Bottom View



Items	Specifications	Conditions
Sound Pressure Level	99	dB (@ 10cm), Avg.
Resonant Frequency	150	Hz
Frequency Range	150 ~ 20,000	Hz
Nominal Power	5	W
Max. Power	6	W
Impedance	4	Ω
Cone Material	Paper	
Mount Type	Flush Mount	
IP Rating	IP65	
Storage Temperature	-40 ~ +85	°C
Operating Temperature	-30 ~ +75	°C
Weight	34	g

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
	Released from Engineering	11/9/2018	C.E.

NOTES			
1) All dimensions are in mm unless otherwise noted			
2) All tolerances are ± 0.5 mm unless otherwise noted			
3) All parts meet RoHS			
4) Subject to change or redrawn without notice			