



DB25F AND TRS WIRING CHART

TRS (CHANNEL)	CABLE (COLOR)	TIP (RED)	RING (BLACK)	SLEEVE (BARE)
1	BROWN	24	12	25
2	RED	10	23	11
3	ORANGE	21	9	22
4	YELLOW	7	20	8
5	GREEN	18	6	19
6	BLUE	4	17	5
7	PURPLE	15	3	16
8	GRAY	1	14	2

NOTES:

- BREAKOUT CABLE LENGTH: 18 +/- 0.75 INCHES. SEE TABLE FOR COLOR.
- THIS PRODUCT COMES COILED AND PACKAGED IN BAG.
- MATERIALS:
 TRS PLUG AND HANDLE - COPPER ALLOY, NICKEL PLATED
 H.S. TUBING - THERMOPLASTIC
 DSUB:
 CABLE CLAMP - COPPER, NICKEL PLATED
 SHELL - STEEL, TIN PLATED
 INSULATORS - THERMOPLASTIC
 SCREW LOCKS - COPPER ALLOY, NICKEL PLATED
- THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

REV	ECO NUMBER	DATE	BY	APVD
C	27520	06/08/15	PC	TJK
B	26637	10/4/10	RS	TJK
A	26568	7/20/10	RS	TJK

REVISIONS

UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS IN INCHES [mm]
 - TWO PLACE DECIMALS ±0.02 [0.5]
 - THREE PLACE DECIMALS ±0.005 [0.13]

DO NOT SCALE DRAWING

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.									
SIZE		WIDTH		MULT		LBS/M		TEMPER	
FINISH					MATERIAL				
SPEC No.					SPEC No.				
FIRST USED ON				SCALE					
				1:2					
DATE DRAWN	BY	CHKD	APVD	Switchcraft [®]					
7/16/09	JGK	RS	TJK						
NAME				PART No.		REV			
DB25F TO 8-TRS, RoHS				DB25FTRS		C			