18 INCHES LENGTH



Connector A 132114RP SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-316 Continuity/Hi-Pot Connector B 132114RP SMA Plug Straight Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

| | Connector A | | | Cable | | Connector B | | |
|---|---------------------------------|--|---|-------------------------------------|------------------------------------|--|--|--|
| Part # | #: 132114R | P | Part #: | RG-316 | Part #: | 132114RP | | |
| Descr | ription: SMA PLU | SMA PLUG RP RG316 500 | | RG-316 - ST 0.102 | Description: | SMA PLUG RP RG316 500 | | |
| Type: | SMA | | Dielectric: | ST | Туре: | SMA | | |
| Gend | er: Plug | | Shielding: | Braid | Gender: | Plug | | |
| Body | Type: Straight | | Diameter: | 0.102 | Body Type: | Straight | | |
| Conta | act Type: Crimp | | Impedance: Sheathing: Testing: | 50 Ohm None Continuity Hi-Pot | Contact Type: | Crimp Reverse 50 Ohm | | |
| Polar | ity: Reverse | | | | Polarity: | | | |
| Imped | dance: 50 Ohm | | | | Impedance: | | | |
| Moun | ting: Cable | | Length: | 18 Inches | Mounting: | Cable | | |
| Body | Material: Brass | | | | Body Material: | Brass | | |
| - | Finish: Gold | | | | Body Finish: | Gold | | |
| IP Rai | ting: None | | | | IP Rating: | None | | |
| Conta | act Material: Beryllium | Beryllium Copper | | | Contact Material: | Beryllium Copper | | |
| Conta | act Finish: Gold | | | | Contact Finish: | Gold | | |
| Max. | Freq.: 12.4 GHz | | | | Max. Freq.: | 12.4 GHz SMA Plug Straight RP 0° | | |
| Booti | | straight RP | | | Booting: | | | |
| | . | , , | | | Clocking: | | | |
| THIS DRAWING MAY CONTAIN PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIMEN | | | Title: SMA-ST-PL-RP/SN | 1A-ST-PL-RP G316 18I | | UNLESS SPECIFIED TOLERANCE: | | |
| ISTOM CARLE | | FOR ANY PURPOSE DETRIMI INC. IT MAY NOT BE REPROI | FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF | | | | 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: | |
| CONTROLLED DOCUME | CONTROLLED DOCUMENT DO NOT CORV | | CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING. | | Part No: O-680680005018I | | CENTER LABEL IF LENGTI IS LESS THAN 12 INCHES | |



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 9/30/2023

Part Number: Q-680680005018I

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-PL-RP/SMA-ST-PL-RP G316 18I

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

Janice Frank