



Directive 2002/95/EC
"RoHS"
Compliant

NOTES:

- METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
- INSULATORS: PBT GF UL 94 V-0, BLACK
- CONTACTS: COPPER ALLOY
PLATING: 8µm HARD GOLD over min. 50µm NICKEL
SOLDER CUP ACCEPTS CABLE AWG 22
- THREADED INSERT: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
- COLLAR: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
- MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
- CONNECTOR IS PART MARKED: 164A17099X CONEC ABC

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH				tolerance		dim. in mm	scale: 2:1 (5:1)			
				date			material: SEE NOTES			
DO NOT ALTER CAD DRAWING BY HAND				drawn	28.03.07	Lehmenkühler	title: D-SUB HD FEMALE 78pos. SOLDER CUP with threaded insert			
				appd.	29.03.07				Mickenbecker	
a Origin				norm		d-old			dwg no: Inventor 10	
				rev. description					date	name
CONEC®							sh: 1			
								part no: 164A17099X		

scale: 2:1 (5:1)	
material: SEE NOTES	
title: D-SUB HD FEMALE 78pos. SOLDER CUP with threaded insert	
dwg no: Inventor 10	DIN-A3
sh: 1	
part no: 164A17099X	