

Plywrap[®] 11

Vinyl Pipewrap

Technical Data Sheet

Printeen Printeen	

October 2017

Description and PLYWRAP® 11, is a corrosion protection, pressure sensitive vinyl tape giving complete **Features** environmental, mechanical and electrical protection for all types of pipe wrapping applications. 0,25 (10 mil) mm thickness High resistant to sun, water, oil, acids, alkalies and corrosive chemicals. Bacteria and fungus resistant. Abrasion resistant. Lead free Meets the requirements of 2000/53/EC and RoHS 2011/65/EU Directives. Product does not contain lead, cadmium, mercury, chromium (VI), polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE), butyl benzyl phthalate (BBP), di(2-ethylhexyl phthalate (DEHP), dibutyl phthalate (DBP) or diisobutyl phthalate (DIBP). **Materials** Backing Adhesive Color Standard Sizes Width x Length PVC Rubber based Black 25 mm x 30 m (1 in. x 100 ft.) 50 mm x 30 m (2 in. x 100 ft.) Other sizes available upon request Characteristic Specification **Technical Properties** Typical Value **Test Method** Thickness, (mm) 0.25±0.03 0.24 **ASTM D 1000**

Breaking strength (N/cm) 44 min 54 **ASTM D 1000** Elongation at break (%) 250 min 270 ASTM D 1000 Adhesion to steel (N/cm) 2,4 min 2,7 ASTM D 1000 Adhesion to backing (N/cm) 2,4 min ASTM D 1000 2,6 Dielectric strength (kV)9,5 min 10 ASTM D 1000 **Recommended Uses** Protect pipes, pipe joints, conduit and couplings in overhead or direct burial applications. Protects from all types of corrosion. In original packaging, placed in horizontal position under cover and temperature between Storage

5°C and 35 °C, 50-80% R.H.

Shelf Life 60 months from date of manufacture.

LIMITED WARRANTY: Plymouth warrants that its Product will substantially conform to that products written specifications for a period of one (1) year from the date of shipment, (Unless provided otherwise). Plymouth makes no warranty to the distributor, its customers, or the product's end user for the product's metabality and/or suitability for his/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall be to REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE. EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products. (Rev. 1/2017-2019)

Plymouth Rubber Europa, S.A. • Ctra. Porriño-Salceda, km 1,5 36400 PORRIÑO - SPAIN • Tel.: +34 986 330 562 • Fax: +34 986 336 926 www.plymouthrubber.com • info@plymouthrubber.com