

3-pin female collector, type 1 3-pin connector, female IPCs Further information, Quantity and content: see technical data



General information	
Product type designation	Power supply unit connector
Control elements	
Frame size/design	
<ul style="list-style-type: none"> Standard 	Yes; Z shape
Installation type/mounting	
Wall mounting/direct mounting	Yes; can be plugged into SIMATIC HMI device
Supply voltage	
Rated value (DC)	24 V; DC
Interfaces	
HMI-side interface	
<ul style="list-style-type: none"> Number of pins HMI-side 	3; Male
Device-side interface	
<ul style="list-style-type: none"> Number of pins device-side 	3; Female, screw terminals
Standards, approvals, certificates	
Use in hazardous areas	
<ul style="list-style-type: none"> ATEX Zone 2 ATEX Zone 22 IECEx Zone 2 IECEx Zone 22 cULus Class I Zone 1 cULus Class I Zone 2, Division 2 FM Class I Division 2 	Yes; Device-dependent, see operating instructions Yes; Device-dependent, see operating instructions Yes; Device-dependent, see operating instructions Yes; Device-dependent, see operating instructions Yes; Device-dependent, see operating instructions Yes; Device-dependent, see operating instructions Yes; Device-dependent, see operating instructions
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> min. max. 	0 °C 55 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> min. max. 	-20 °C 70 °C
Relative humidity	
<ul style="list-style-type: none"> Operation, max. 	95 %
Mechanics/material	
Material	
<ul style="list-style-type: none"> Plastic 	Yes; green
Screw type	
<ul style="list-style-type: none"> 4.5 V 	Yes; Screw terminals
Dimensions	

Width	15.5 mm
Height	27 mm
Thickness	15 mm
Scope of supply	
Delivery quantity in pieces	5
Other	
Merchandise	Yes
Manufacturer name	SIEMENS AG
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany
Target devices	For IPC and thin client with corresponding interface
last modified:	3/12/2021 