

72 INCHES LENGTH



Connector A
132119
SMA Jack Straight
Bulkhead - Rear Mount Brass Gold + Heatshrink

50 Ohm RG-174
Continuity/Hi-Pot

Connector B
082-6575
N-Type Jack Straight
Bulkhead - Rear Mount Brass Nickel IP67 + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink
Assembly shall be built with SN96.5 LEAD FREE solder.
See Routing Notes for additional assembly & testing instructions.

Connector A		Cable		Connector B	
Part #:	132119	Part #:	RG-174	Part #:	082-6575
Description:	SMA BHD JK RG174 RG188 RG316 50O	Description:	RG-174 - PE 0.1	Description:	N-Type BHD JK RG316 IP67 50O
Type:	SMA	Dielectric:	PE	Type:	N-Type
Gender:	Jack	Shielding:	Braid	Gender:	Jack
Body Type:	Straight	Diameter:	0.1	Body Type:	Straight
Contact Type:	Solder	Impedance:	50 Ohm	Contact Type:	Solder
Polarity:	Standard	Sheathing:	None	Polarity:	Standard
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm
Mounting:	Bulkhead - Rear Mount	Length:	72 Inches	Mounting:	Bulkhead - Rear Mount
Body Material:	Brass			Body Material:	Brass
Body Finish:	Gold			Body Finish:	Nickel
IP Rating:	None			IP Rating:	IP67
Contact Material:	Beryllium Copper			Contact Material:	Beryllium Copper
Contact Finish:	Gold			Contact Finish:	Gold
Max. Freq.:	12.4 GHz			Max. Freq.:	11 GHz
Booting:	SMA Jack Straight BHD			Booting:	N-Type Jack Straight BHD
				Clacking:	0°



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:
SMA-ST-JK/N-ST-JK G174 72I

Part No:
Q-2W01U0003072I

UNLESS SPECIFIED
TOLERANCE:
0-18 inches +/- 1/2"
over 18" +/- 2%
ASSEMBLY:
CENTER LABEL IF LENGTH
IS LESS THAN 12 INCHES