


REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	10/12/12	D.N.






NOTES:

MATERIALS:

1. BODY = STAINLESS STEEL PER ASTM A582, ALLOY 303, CONDITION "A".
2. INSULATOR = VIRGIN WHITE TEFLON PER ASTM D1710, GRADE 1, TYPE I, CLASS "B".
3. CONTACT = BERYLLIUM COPPER PER ASTM B196, ALLOY C17300, TEMPER TD04.

FINISHES:

1. BODY = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 0, GRADE C, OVER .000050 TO .00010 STRESS FREE NICKEL PER QQ-N-290.
2. CONTACT = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 1, GRADE C, OVER .00010 TO .00020 STRESS FREE SULFAMATE NICKEL PER QQ-N-290.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON	DWN:	DATE	 Property of Radiall This document cannot be reproduced or communicated to a third party without prior written permission of RADIALL.	
	D.N.	10/12/12		
DECIMAL	ANGLE	CHKD:	DATE	SMA STRAIGHT JACK TO STRIPLINE NON-CAPTIVE CONTACT
		J.S.	10/12/12	
		APVD:	DATE	SIZE A FSCM NO. 19505 DWG NO. 9003-1213-003 REV A
		J.M.	10/12/12	
REFERENCE:	MATERIALS & FINISHES:	SEE NOTES		SCALE 5:1 THIRD ANGLE PROJECTION
ORIGINATED: D.N. DATE: 10/12/12				 SHEET 1 OF 1

9003-1213-003