6 INCHES LENGTH



Connector A 132119 SMA Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 919-387P-51A MCX Plug Right Angle Brass Gold-Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Right Angle	Connector A			Cable			Connector B		
135° 45° 180° 7° 315° 225° 270° 315° Eulkhead	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	132119 SMA BHD JK RG174 RG188 RG316 500 SMA Jack Straight Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Straight BHD		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 6 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	919-387P-51A MCX R/A PLUG RG MCX Plug Right Angle Solder Standard 50 Ohm Cable Brass Gold-Nickel None Brass Gold 6 GHz MCX Plug Right An 0°	9174 RG188 RG316 500	
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT DO NOT CORV			PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIME INC. IT MAY NOT BE REPROD IN ANY FORM WITHOUT THE CUSTOM CABLE INC. ACCEPT	DRAWING MAY CONTAIN PATENTED OR RETARY INFORMATION AND MUST NOT BE USED NY PURPOSE DETRIMENTAL TO CUSTOM CABLE T MAY NOT BE REPRODUCED OR TRANSCRIBED Y FORM WITHOUT THE WRITTEN CONSENT OF DM CABLE INC. ACCEPTANCE OF THIS DRAWING RUSHES AND AGREEMENT OF THE FOREGOING.		Title: SMA-ST-JK/MCX-RA-PL G174 6I Part No: Q-2W01A0003006I			