



Product Description

Security & Sound Cable, Plenum-CMP, 2-22 AWG solid bare copper pairs with Flamarrest® insulation, Beldfoil® shield and Flamarrest® jacket with ripcord

Technical Specifications

Product Overview

Suitable A	pplications:		Security	/ System, Inte	ercom/PA, Audio/Spe	aker, Power-Limited Controls, N	Noisy Environment
Constru	ction Detai	Is					
Conductor							
Element	No. of Element	s Size	Stranding	Materi	al		
Pair(s)	2	22 AWG	Solid	BC - Bare	Copper		
nsulation							
Element	Materia	I N	om. Thickr	ness Nom.	Insulation Diameter	Color Code	
Pair(s)	PVC - Polyvinyl	Chloride 0.	009 in (0.23	mm) 0.044	in (1.1 mm)	Black & Red, Black & White	
Outer Shiel	Id						
		6	0	Dustaut			
Shield Typ		terial	Coverag		ге Туре		
Гаре	Bi-Laminate	e (Alum+Poly) 100%	24 AWG	(7x32) TC		
Outer Jacket							
Ma	aterial	Nom. Thick	ness No	n. Diameter	Ripcord		
PVC - Poly	yvinyl Chloride	0.015 in (0.3	8 mm) 0.1	93 in	Yes		
Overall Ca	able Diameter (N	lominal):	0.193 ir	1			
Electrical Characteristics							

Electricals

Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current	
18.7 Ohm/1000ft	34 pF/ft (110 pF/m)	61.2 pF/ft (201 pF/m)	4.8 Amps per Conductor at 30°C	

Voltage

UL Voltage Rating 300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	0°C to +75°C

Bend Radius

Stationary Min.Installation Min.1.93 in (49.0 mm)1.93 in

Max. Pull Tension:	36.7 lbs (16.6 kg)
Bulk Cable Weight:	19 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor	
Flammability / Reaction to Fire:	NFPA 262 (UL 910), FT6	
NEC / UL Compliance:	Article 800, CMP	
CEC / C(UL) Compliance:	СМР	
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	
Non-Plenum Number:	5561FE	

History

Update and Revision:

Revision Number: 0.312 Revision Date: 05-05-2023

Part Numbers

Variants

Item #	Color	UPC	Footnote
6561FE 8771000	Natural	612825178590	С

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.