



Accepts .020 (0.5) to .041 (1.05) Dia. Center Conductor Typical

3/8-32UNEF-2A

1.043 (26.5) Ref.

NOTES: Finish (Plating Thickness in Micro-inches)

- 1. Brass
- 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
- 3. Phosphor Bronze
- 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
- 5. TEFLON
- 6. BERYLLIUM COPPER

RoHS Compliant

Dimensions are in Inches										Part No.		NTE Electronics	
Unless Otherwise Specified Tolerances										Approved			
0.5-6 = ±0.2												2-16-2011	
6-30 = ±0.4										Checked		Date	
30-120 = ±0.6												2-16-2011	
120-315 = ±1										Drawn		Date	
315-1000 = ±1.6												2-16-2011	
1000-2000 = ±2.4													
Title										BNC Female to F Female Adapter			
Drawing No.										06-B027			
File No.													

No	Description	Material	Finish	Q'ty	Drawing No.
6	Body	Note 1	Note 2	1	
5	Insulator	Note 5	Natural	1	
4	Contact Pin	Note 6	Note 4	1	
3	Contact Pin	Note 3	Note	1	
2	Insulator	Note 5	Natural	1	
1	Housing	Note 1	Note 2	1	

F
E
D
C
B
A

F
E
D
C
B
A

1 2 3 4 5 6 7 8

1 2 3 4 5 6 7 8