



B1323(S)

Omnidirectional Antennas 132-525MHz

FEATURES AND BENEFITS

- 5/8 wave design for true 3 dBi performance
- Easy installation with optional NMO mounts
- Special UV-treated radome; resists sun damage
- 100% tested on a network analyzer


APPLICATIONS

- Mobile
- Amateur
- P25
- Public safety

ELECTRICAL SPECIFICATIONS

Operating Frequency (MHz)	132 - 525
Number of Ports	1
VSWR	<2:1
Gain (dBi)	3
Nominal Impedance (Ohms)	50
Max Power - Ambient 25°C (W)	100
Polarization	Vertical
Pattern	Omnidirectional
Half-Power Beamwidth (Elevation° x Azimuth°)	70° x 360°
Noise Suppressor	BlackHawk NS1535 1-35 VOLT, 15 Amp Noise Suppressor (Sold Separately) 

MECHANICAL SPECIFICATIONS


Height - cm (inches)	144.8 (57.0) (see Cutting Chart)
Diameter - cm (inches)	3.66 (1.44)
Weight - kg (lbs.)	0.23 (0.5)
Equivalent Flat Plane Area (Wind Resistance - ft ²)	0.025
Coaxial Cable Length and Type	None
Termination	NMO
Mounting	< 1000 MHz - PN: MB8, MAB8 DC to 6 GHz - PN: MB195 

B1323 CUTTING


FREQUENCY	WHIP LENGTH	FREQUENCY	WHIP LENGTH
132	54-7/16"	154	43-3/4"
134	53-7/16"	156	43"
136	52-1/16"	158	42-1/4"
138	51-1/8"	160	41-5/8"
140	50-1/8"	162	41"
142	49-1/4"	164	40-3/8"
144	48"	166	39-3/8"
146	47-1/4"	168	38-3/8"
148	46-1/4"	170	37-3/8"
150	45-3/8"	172	36-5/8"
152	44-1/2"	174	35-7/8"

B1323S CUTTING

FREQUENCY	WHIP LENGTH	FREQUENCY	WHIP LENGTH
132	52-7/8"	154	41-3/8"
134	51-15/16"	156	40-3/8"
136	50-3/8"	158	39-5/8"
138	49-1/8"	160	38-3/4"
140	48-1/8"	162	37-15/16"
142	47-1/4"	164	37-1/8"
144	46"	166	36-1/4"
146	45-1/8"	168	35-7/16"
148	43-7/8"	170	34-5/8"
150	43"	172	33"
152	42-1/4"	174	33"



VSWR OF B1323(S)



B1323 Typical VSWR sweeps on a 4'x4' Ground Plane

- Marker 1:** 1.2665 to 1@ 132.000 MHz
- Marker 2:** 2.5264 to 1@ 125.518 MHz
- Marker 3:** 2.4930 to 1@ 138.583 MHz

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warranted to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original