


21XXXX515-XX  
Code  
Pin Number

2 Pin	P/N: 21002515-02	P/N: 21003515-02	P/N: 21004515-06
Pin Assignments Front View			



- Specification:
1. Operation Temperature:  $-45^{\circ}\text{C} \sim 105^{\circ}\text{C}$ .
  2. Insulation Resistance:  $100\text{M}\Omega$  at DC 500V.
  3. Contact Resistance:  $<10\text{m}\Omega$ .
  4. Withstand Voltage: 1500V AC.
  5. Operating Current: 5A.
  6. Operating Voltage: AC 110V.
  7. Waterproof Rate: IP67 (Mated).
  8. Connector: Nylon+GF, Black.
  9. Panel Nut: Nylon, Black.
  10. Gasket: Silicon, Gray.
  11. Male Pin: Copper Alloy Gold Plated.
  12. Torque Rate:  $0.5 \sim 0.7\text{N}\cdot\text{m}$ .
  13. RoHS Compliant.
  14. UL Compliant.
  15. Mating Cap P/N: 806-00028-00

UNIT: mm

TOLERANCE	Front Mount With Male Pin(PCB)	
.X	$\pm 0.25$	SCALE: 4:5
.XX	$\pm 0.15$	REV: C1
.XXX	$\pm 0.05$	SIZE: A4
ANGLES	$\pm 1^{\circ}$	SHEET: 1 OF 1
		* : Inspection Item

REV.	EN. NO.	DESCRIPTION	SIGN	DATE
C1	N/A	INITIAL DRAWING	Victory	2019/08/21

DESCRIPTION	Mini Series Screw Type	PART NO	21XXXX515-XX	DRAWN BY	Victory	DATE	2019/08/21
SCALE	4:5	DWG NO		CHECKED BY	Ivan	DATE	2019/08/21
REV	C1	CUSTOMER		APPROVED BY	Ponson	DATE	2019/08/21

**CHOGORI**