REV.	DATE	DESCRIPTION
A	05/16/03	MOPDIFY PART DESCRIPTION



RECOMMENDED
CABLE STRIPPING DIM'S







CRIMP NOTES:

1. CRIMPED FERRULE
   HEX CRIMP SIZE .429"
2. CRIMPED CONTACT PIN
   HEX CRIMP SIZE .100"

8				
7				
6				
5				
4	FERRULE	COPPER	NEXCOTE	1
3	CONTACT PIN	BRASS	GOLD	1
2	INSULATOR	TEFLON	NATURAL	1
1	SHELL/BODY	BRASS	NEXCOTE	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN G.R.S.	05/16/03
CHECKED	
ISSUED	
SHEET 1 OF 1	

CAD FILE C:/172/172102NEX–10.DWG

Amphenol Connex

PART DESCRIPTION
N CRIMP PLUG, HEX NUT
(FOR RG–8/U, 213/U, 393/U CABLE)

PART NO. 172102NEX–10

DWG. NO.	REV.	SIZE	SCALE
172102NEX–10.DWG	A	A	NA