



UNIT:MM

P1		P2	
1	WHITE	1	WHITE
2	GREY	15	YELLOW
3	YELLOW	13	PINK
4	PINK	12	ORANGE
5	ORANGE	10	RED
6	RED	11	BROWN
7	BROWN	5	GREEN
8	GREEN	4	BLUE
9	BLUE	3	PURPLE
10	PURPLE	4	LIGHT/GREEN
11	LIGHT/GREEN	14	LIGHT/BLUE
12	LIGHT/BLUE	2	BLACK
13	BLACK	16	WHITE/BLACK
14	WHITE/BLACK	17	GRAY/BLACK
15	GRAY/BLACK	25	DRAIN
16	DRAIN	25	SHELL
17	SHELL	25	SHELL
18	SHELL	25	SHELL

Electrical test:
 1. 100% short, open, miswire test
 2. Conduct resistance: 2 Ohm(max)
 3. Insulation resistance: 5Mohm(min)
 4. dielectric test: DC 300V

①	PE BAG	1/10	CLEAR SIZE: 360*380*0.05mm PRINT BLACK"MADE IN CHINA"+"10PCS"
②	PE BAG	1	CLEAR SIZE: 150*280*0.05mm PRINT BLACK"MADE IN CHINA"+"1PC"
③	TIE	2	WHITE L=100MM
④	S/R	5.5g	BEIGE(IV-29#) 45P PVC (MOULD NO.SR-51)
⑤	TUBE	2	黑色热缩套管, OD1.5mm,L=30mm
⑥	SCREW	4	SCREW #4-40UNC L=12.5mm,NICKEL PLATED
⑦	DKN	2	DB25P DKN W/O NUT BEIGE
⑧	CABLE	1	NOUL 30AWG*15C+AE OD6.0mm COLOR BEIGE(IV-29#)
⑨	CONN	2	DB25P MALE SOLDER TYPE PIN G/F. BLUE INSULATION
NO.	NAME	QTY	SPECIFICATION

CNC Tech, LLC
 Industrial Cable and Connector Technology

DRAWN BY	ZHONGHS	DRAWING NO.	
CHECKED BY		CUSTOMER	
APPROVAL BY		ITEM NO.	720-10049-00300
DECIDE BY		DATE	2012-02-06
VERSIONS/EDITION	A/0	PROJECT	

4

3

2

1