

N-Channel 20-V (D-S) MOSFETs

PRODUCT SUMMARY

	V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A)	Q _g (Typ.)
Channel-1	20	0.0086 at V _{GS} = 10 V	16 ^a	9.5 nC
		0.0108 at V _{GS} = 4.5 V	16 ^a	
Channel-2	20	0.0058 at V _{GS} = 10 V	16 ^a	27 nC
		0.0066 at V _{GS} = 4.5 V	16 ^a	

FEATURES

- Halogen-free According to IEC 61249-2-21 Definition
- TrenchFET® Power MOSFETs
- 100 % R_g Tested
- Compliant to RoHS Directive 2002/95/EC




RoHS
COMPLIANT
HALOGEN
FREE

APPLICATIONS


- Notebook System Power
- POL

PowerPAIR® 6 x 3.7



Ordering Information:

SiZ700DT-T1-GE3 (Lead (Pb)-free and Halogen-free)



ABSOLUTE MAXIMUM RATINGS (T_A = 25 °C, unless otherwise noted)

Parameter		Symbol	Channel-1	Channel-2	Unit
Drain-Source Voltage		V _{DS}	20	20	V
Gate-Source Voltage		V _{GS}	± 16		
Continuous Drain Current (T _J = 150 °C)	T _C = 25 °C	I _D	16 ^a	16 ^a	A
	T _C = 70 °C		16 ^a	16 ^a	
	T _A = 25 °C		13.1 ^{b, c}	17.3 ^{b, c}	
	T _A = 70 °C		10.5 ^{b, c}	13.9 ^{b, c}	
Pulsed Drain Current		I _{DM}	60	60	
Source Drain Current Diode Current	T _C = 25 °C	I _S	14.7	16 ^a	
	T _A = 25 °C		1.96 ^{b, c}	2.3 ^{b, c}	
Maximum Power Dissipation	T _C = 25 °C	P _D	2.36	2.8	W
	T _C = 70 °C		1.5	1.78	
	T _A = 25 °C		1.4 ^{b, c}	1.47 ^{b, c}	
	T _A = 70 °C		0.9 ^{b, c}	0.94 ^{b, c}	
Operating Junction and Storage Temperature Range		T _J , T _{stg}	- 55 to 150		°C
Soldering Recommendations (Peak Temperature) ^{d, e}			260		

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Channel-1		Channel-2		Unit
		Typ.	Max.	Typ.	Max.	
Maximum Junction-to-Ambient ^{b, f}	R _{thJA}	39	53	33	45	°C/W
Maximum Junction-to-Case (Drain)	R _{thJC}	5.7	7.1	3.7	4.6	

Notes:

a. Package limited.

b. Surface mounted on 1" x 1" FR4 board.

c. t = 10 s.

d. See solder profile (www.vishay.com/doc?73257). The PowerPAIR is a leadless package. The end of the lead terminal is exposed copper (not plated) as a result of the singulation process in manufacturing. A solder fillet at the exposed copper tip cannot be guaranteed and is not required to ensure adequate bottom side solder interconnection.

e. Rework conditions: manual soldering with a soldering iron is not recommended for leadless components.

f. Maximum under steady state conditions is 90 °C/W for channel-1 and 85 °C/W for channel-2.

SPECIFICATIONS (T _J = 25 °C, unless otherwise noted)								
Parameter	Symbol	Test Conditions		Min.	Typ.	Max.	Unit	
Static								
Drain-Source Breakdown Voltage	V _{DS}	V _{GS} = 0 V, I _D = 250 μA	Ch-1	20			V	
		V _{GS} = 0 V, I _D = 250 μA	Ch-2	20				
V _{DS} Temperature Coefficient	ΔV _{DS} /T _J	I _D = 250 μA	Ch-1		21		mV/°C	
		I _D = 250 μA	Ch-2		21			
V _{GS(th)} Temperature Coefficient	ΔV _{GS(th)} /T _J	I _D = 250 μA	Ch-1		- 5.8			
		I _D = 250 μA	Ch-2		- 5.8			
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	Ch-1	0.8		2.2	V	
		V _{DS} = V _{GS} , I _D = 250 μA	Ch-2	0.8		2.2		
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ± 16 V	Ch-1			± 100	nA	
			Ch-2			± 100		
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 20 V, V _{GS} = 0 V	Ch-1			1	μA	
		V _{DS} = 20 V, V _{GS} = 0 V	Ch-2			1		
		V _{DS} = 20 V, V _{GS} = 0 V, T _J = 55 °C	Ch-1			10		
		V _{DS} = 20 V, V _{GS} = 0 V, T _J = 55 °C	Ch-2			10		
On-State Drain Current ^b	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 10 V	Ch-1	30			A	
		V _{DS} ≥ 5 V, V _{GS} = 10 V	Ch-2	30				
Drain-Source On-State Resistance ^b	R _{DS(on)}	V _{GS} = 10 V, I _D = 15 A	Ch-1		0.007	0.0086	Ω	
		V _{GS} = 10 V, I _D = 20 A	Ch-2		0.0047	0.0058		
		V _{GS} = 4.5 V, I _D = 10 A	Ch-1		0.0088	0.0108		
		V _{GS} = 4.5 V, I _D = 15 A	Ch-2		0.0054	0.0066		
Forward Transconductance ^b	g _{fs}	V _{DS} = 10 V, I _D = 15 A	Ch-1		60		S	
		V _{DS} = 10 V, I _D = 20 A	Ch-2		100			
Dynamic ^a								
Input Capacitance	C _{iss}	Channel-1 V _{DS} = 10 V, V _{GS} = 0 V, f = 1 MHz	Ch-1		1300		pF	
			Ch-2		3860			
Output Capacitance	C _{oss}		Ch-1		290			
			Ch-2		760			
Reverse Transfer Capacitance	C _{rss}	Channel-2 V _{DS} = 10 V, V _{GS} = 0 V, f = 1 MHz	Ch-1		132			
			Ch-2		350			
Total Gate Charge	Q _g	V _{DS} = 10 V, V _{GS} = 10 V, I _D = 15 A	Ch-1		20	35	nC	
		V _{DS} = 10 V, V _{GS} = 10 V, I _D = 20 A	Ch-2		55	85		
		Channel-1 V _{DS} = 10 V, V _{GS} = 4.5 V, I _D = 15 A	Ch-1		9.5	15		
			Ch-2		27	45		
Gate-Source Charge	Q _{gs}	Channel-2 V _{DS} = 10 V, V _{GS} = 4.5 V, I _D = 20 A	Ch-1		3.2			
			Ch-2		9.2			
Gate-Drain Charge	Q _{gd}		Ch-1		2.4			
			Ch-2		7.1			
Gate Resistance	R _g	f = 1 MHz	Ch-1	0.3	1.3	2.6	Ω	
			Ch-2	0.2	1	2		

Notes:

a. Guaranteed by design, not subject to production testing.

b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.









SPECIFICATIONS (T _J = 25 °C, unless otherwise noted)								
Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit		
Dynamic ^a								
Turn-On Delay Time	t _{d(on)}	Channel-1 V _{DD} = 10 V, R _L = 10 Ω I _D ≅ 1 A, V _{GEN} = 4.5 V, R _g = 1 Ω	Ch-1		9	15	ns	
			Ch-2		13	20		
Rise Time	t _r		Ch-1		8	15		
			Ch-2		8	15		
Turn-Off Delay Time	t _{d(off)}	Channel-2 V _{DD} = 10 V, R _L = 10 Ω I _D ≅ 1 A, V _{GEN} = 4.5 V, R _g = 1 Ω	Ch-1		25	40		
			Ch-2		52	80		
Fall Time	t _f		Ch-1		8	15		
			Ch-2		15	25		
Turn-On Delay Time	t _{d(on)}	Channel-1 V _{DD} = 10 V, R _L = 10 Ω I _D ≅ 1 A, V _{GEN} = 10 V, R _g = 1 Ω	Ch-1		8	15		
			Ch-2		12	20		
Rise Time	t _r		Ch-1		9	15		
			Ch-2		8	15		
Turn-Off Delay Time	t _{d(off)}	Channel-2 V _{DD} = 10 V, R _L = 10 Ω I _D ≅ 1 A, V _{GEN} = 10 V, R _g = 1 Ω	Ch-1		25	40		
			Ch-2		47	75		
Fall Time	t _f		Ch-1		8	15		
			Ch-2		10	15		
Drain-Source Body Diode Characteristics								
Continuous Source-Drain Diode Current	I _S	T _C = 25 °C	Ch-1			14.7	A	
			Ch-2			16		
Pulse Diode Forward Current ^a	I _{SM}		Ch-1			60		
			Ch-2			60		
Body Diode Voltage	V _{SD}	I _S = 2 A, V _{GS} = 0 V	Ch-1		0.8	1.2	V	
		I _S = 2.3 A, V _{GS} = 0 V	Ch-2		0.8	1.2		
Body Diode Reverse Recovery Time	t _{rr}	Channel-1 I _F = 2 A, dI/dt = 100 A/μs, T _J = 25 °C	Ch-1		25	50	ns	
			Ch-2		40	80		
Body Diode Reverse Recovery Charge	Q _{rr}		Channel-2 I _F = 2.3 A, dI/dt = 100 A/μs, T _J = 25 °C	Ch-1		13	25	nC
				Ch-2		31	60	
Reverse Recovery Fall Time	t _a	Channel-2 I _F = 2.3 A, dI/dt = 100 A/μs, T _J = 25 °C		Ch-1		12		ns
				Ch-2		21		
Reverse Recovery Rise Time	t _b		Channel-2 I _F = 2.3 A, dI/dt = 100 A/μs, T _J = 25 °C	Ch-1		13		
				Ch-2		19		

Notes:


a. Guaranteed by design, not subject to production testing.

b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\text{ }\%$.


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

CHANNEL-1 TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)**Output Characteristics****Transfer Characteristics****On-Resistance vs. Drain Current****Capacitance****Gate Charge****On-Resistance vs. Junction Temperature**


CHANNEL-1 TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage





Single Pulse Power




* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified

Safe Operating Area, Junction-to-Ambient

CHANNEL-1 TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)**Current Derating***


T_C - Case Temperature (°C)
Power, Junction-to-Case




T_A - Ambient Temperature (°C)
Power, Junction-to-Ambient

* The power dissipation P_D is based on $T_{J(max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.







CHANNEL-1 TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)




Normalized Thermal Transient Impedance, Junction-to-Ambient




Normalized Thermal Transient Impedance, Junction-to-Case

CHANNEL-2 TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)**Output Characteristics****Transfer Characteristics****On-Resistance vs. Drain Current****Capacitance****Gate Charge****On-Resistance vs. Junction Temperature**


CHANNEL-2 TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage





Single Pulse Power




* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified

Safe Operating Area, Junction-to-Ambient

CHANNEL-2 TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)**Current Derating***


T_C - Case Temperature (°C)
Power, Junction-to-Case




T_A - Ambient Temperature (°C)
Power, Junction-to-Ambient

* The power dissipation P_D is based on $T_{J(max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

CHANNEL-2 TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)




Normalized Thermal Transient Impedance, Junction-to-Ambient



Normalized Thermal Transient Impedance, Junction-to-Case

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?69090.

PowerPAIR™ 6 x 3.7 CASE OUTLINE



DIM.	MILLIMETERS			INCHES		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	0.70	0.75	0.80	0.028	0.030	0.032
A1	0.00	-	0.05	0.000	-	0.002
b	0.46	0.51	0.56	0.018	0.020	0.022
b1	0.20	0.25	0.38	0.008	0.010	0.015
C	0.18	0.20	0.23	0.007	0.008	0.009
D	3.65	3.73	3.81	0.144	0.147	0.150
D1	2.41	2.53	2.65	0.095	0.100	0.104
E	5.92	6.00	6.08	0.233	0.236	0.239
E1	2.62	2.67	2.72	0.103	0.105	0.107
E2	0.87	0.92	0.97	0.034	0.036	0.038
e	1.27 BSC			0.05 BSC		
K	0.45 TYP.			0.018 TYP.		
K1	0.66 TYP.			0.026 TYP.		
K2	0.60 TYP.			0.024 TYP.		
L	0.38	0.43	0.48	0.015	0.017	0.019
ECN: S-82772-Rev. B, 17-Nov-08 DWG: 5979						

Technical drawing of a mechanical part, showing dimensions in inches and millimeters. The drawing includes a central rectangular feature with a width of 0.1040 (2.642) and a height of 0.1070 (2.718). The central feature has a vertical centerline and a horizontal centerline, with a tolerance of 0, 0.03 indicated. The overall width of the part is 0.3520 (8.941). The overall height is 0.4390 (11.151). The drawing also shows several smaller rectangular features and a large rectangular feature at the bottom with a width of 0.0500 (1.27) and a height of 0.0380 (0.965). The drawing includes a large number '1' in the bottom left corner.

Dimensions (Inches / Millimeters):

- Overall Width: 0.3520 (8.941)
- Overall Height: 0.4390 (11.151)
- Top Section Width: 0.0220 (0.559)
- Top Section Height: 0.0190 (0.483)
- Top Section Tolerance: 0, 0.11
- Central Feature Width: 0.1040 (2.642)
- Central Feature Height: 0.1070 (2.718)
- Central Feature Tolerance: 0, 0.03
- Central Feature Horizontal Tolerance: 0, 0
- Bottom Section Width: 0.0500 (1.27)
- Bottom Section Height: 0.0380 (0.965)
- Bottom Section Tolerance: 0, -0.11
- Bottom Section Horizontal Tolerance: -0.05, -0.11
- Bottom Section Vertical Tolerance: 0.0170 (0.432)
- Bottom Section Horizontal Tolerance: 0.0220 (0.559)

www.vishay.com



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.