9007AW32M16 LIMIT SWITCH 600VAC 15AMP AW +OPTIONS



Main

Body type	Standard
Device short name	AW
Series name	Heavy duty

Complementary

Complementary		
Line Rated Current	15 A	
Body material	Cast zinc	
Contact operation	Snap action	
Fluid connection type	0.5 inch BSP conduit entrance	
Impregnation material	Oil	
Mounting location	Front Rear	
Operating Distance	0.190.31 inch	
Operating travel	0.05 In (1.27 mm) 0.09 in (2.29 mm)	
Size	Roller 0.63 x 0.25 inch	
Switch actuation	Horizontal	
Torque Value	3 lbf.in (0.34 N.m)	
Type of operator	Spring return roller	

Environment

Ambient Air Temperature for Operation	0185 °F (-1885 °C)
NEMA Degree of Protection	NEMA 1/2/4/12/13
Product Certifications	CE
	CSA LR25490 class 3211 03 UL listed file E42259 CCN NKCR

Ordering and shipping details

Category	21496-9007 AW PRECISION LIMIT SWITCHES
Discount Schedule	DS1
GTIN	3606485328492
Returnability	No
Country of origin	MX

Packing Units

PCE
1
1.70 in (4.318 cm)
2.80 in (7.112 cm)
5.20 in (13.208 cm)
20.00 oz (566.991 g)
-

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months