



General ordering data

Order No.	1793190000
Part designation	SC 3.81/10/90G 3.2SN BK BX
Version	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 10, 90°, Box
EAN	4032248227686
Qty.	50 pc(s).

System parameters

Fitted to PCB	Soldered connection
Outgoing elbow	90°
Pitch	3.81 mm
Pitch in inch	0.15 inch
No. of poles	10
Solder pin length	3.2 mm
Can be coded	Yes
No. of rows	1
No. of solder pins per pole	1
Dia. of fitting hole	1.2 mm
Fitting hole tolerance	+ 0.1 mm
L1 in mm	34.29 mm
L1 in inch	1.35 inch
Insulation resistance	1,000 MΩ
Electric shock protection to DIN VDE 0470	IP 20
Electric shock protection to DIN VDE 0470	Safe from finger touch

Material data

Insulating material	PA GF
Colour	black
colour chart	Similar to RAL 9011
Insulating material group	II
Flammability class UL 94	V-0
CTI	>= 475
Contact base material	Copper alloy

Material data

Contact surface	tinned
Constant operating temp., min.	-25 °C
Constant operating temp., max.	120 °C
Storage temperature, min.	-25 °C
Storage temperature, max.	55 °C
Max. relative humidity during storage	93 %

DIN IEC rating data

Rated current, min. No. pins (Tu=20°C)	17.5 A
Rated current, min. No. pins(Tu=40°C)	17.5 A
Rated voltage for overvoltage class/pollution severity III/3	160 V
Rated impulse withstand voltage for overvoltage class/pollution severity III/3	2.5 kV
Rated voltage for overvoltage class/pollution severity III/2	160 V
Rated impulse withstand voltage for overvoltage class/pollution severity III/2	2.5 kV
Rated voltage for overvoltage class/pollution severity II/2	320 V
Rated impulse withstand voltage for overvoltage class/pollution severity II/2	2.5 kV
Short-time withstand current resistance	3 x 1s with 76 A

CSA rating data

Rated voltage (Use group D)	300 V
Rated current (Use group D)	10 A

UL 1059 rating data

Rated voltage (Use group D)	300 V
Rated current (Use group D)	10 A

Approvals

Approvals institutes



Classifications

eClass 4.1	27-26-07-01
eClass 5.0	27-26-07-01
eClass 5.1	27-26-07-04

Similar products

Order No.	Part designation	Version
1942020000	SC 3.81/02/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 2, 90°, Box

1793130000	SC 3.81/02/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 2, 90°, Box
1793240000	SC 3.81/02/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 2, 90°, Box
1942040000	SC 3.81/03/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 3, 90°, Box
1793140000	SC 3.81/03/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 3, 90°, Box
1793250000	SC 3.81/03/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 3, 90°, Box
1942070000	SC 3.81/04/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 4, 90°, Box
1793150000	SC 3.81/04/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 4, 90°, Box
1793260000	SC 3.81/04/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 4, 90°, Box
1942090000	SC 3.81/05/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 5, 90°, Box
1793160000	SC 3.81/05/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 5, 90°, Box
1793270000	SC 3.81/05/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 5, 90°, Box
1942100000	SC 3.81/06/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 6, 90°, Box
1793170000	SC 3.81/06/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 6, 90°, Box
1793280000	SC 3.81/06/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 6, 90°, Box
1942120000	SC 3.81/07/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 7, 90°, Box
1942350000	SC 3.81/07/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 7, 90°, Box
1942260000	SC 3.81/07/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 7, 90°, Box
1942130000	SC 3.81/08/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 8, 90°, Box
1793180000	SC 3.81/08/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 8, 90°, Box
1793290000	SC 3.81/08/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 8, 90°, Box
1942140000	SC 3.81/09/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 9, 90°, Box
1942360000	SC 3.81/09/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 9, 90°, Box
1942270000	SC 3.81/09/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 9, 90°, Box
1942150000	SC 3.81/10/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 10, 90°, Box
1793300000	SC 3.81/10/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 10, 90°, Box
1942160000	SC 3.81/11/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 11, 90°, Box

1942370000	SC 3.81/11/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 11, 90°, Box
1942280000	SC 3.81/11/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 11, 90°, Box
1942170000	SC 3.81/12/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 12, 90°, Box
1793200000	SC 3.81/12/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 12, 90°, Box
1793310000	SC 3.81/12/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 12, 90°, Box
1942180000	SC 3.81/13/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 13, 90°, Box
1942380000	SC 3.81/13/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 13, 90°, Box
1942290000	SC 3.81/13/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 13, 90°, Box
1942190000	SC 3.81/14/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 14, 90°, Box
1942390000	SC 3.81/14/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 14, 90°, Box
1808990000	SC 3.81/14/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 14, 90°, Box
1942200000	SC 3.81/15/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 15, 90°, Box
1942400000	SC 3.81/15/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 15, 90°, Box
1942300000	SC 3.81/15/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 15, 90°, Box
1942210000	SC 3.81/16/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 16, 90°, Box
1793210000	SC 3.81/16/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 16, 90°, Box
1793320000	SC 3.81/16/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 16, 90°, Box
1942220000	SC 3.81/17/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 17, 90°, Box
1942410000	SC 3.81/17/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 17, 90°, Box
1942310000	SC 3.81/17/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 17, 90°, Box
1942230000	SC 3.81/18/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 18, 90°, Box
1942420000	SC 3.81/18/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 18, 90°, Box
1942320000	SC 3.81/18/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 18, 90°, Box
1942240000	SC 3.81/19/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 19, 90°, Box
1942430000	SC 3.81/19/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 19, 90°, Box
1942330000	SC 3.81/19/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 19, 90°, Box

1942250000	SC 3.81/20/90G 3.2SN OR BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 20, 90°, Box
1942440000	SC 3.81/20/90G 3.2SN BK BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 20, 90°, Box
1942340000	SC 3.81/20/90G 3.2SN GN BX	PCB plug-in connector, Male connectors, Soldered connection, Pitch: 3.81 mm, No. of poles: 20, 90°, Box