

6 5 4 3 2 1

E

D

C

B

A

F3 MAX-LOC NUT

STAINLESS STEEL
SCREWS W/FLAT
WASHER 1ST
AND O'RING

STAINLESS STEEL
SCREWS W/LOCK
WASHER
(8) REQ'D

STAINLESS STEEL
SUPPORT RINGS
(2) REQ'D

14.50
(368.3)

POSITION 1 & 2 (SINGLE SPEED)
(505SW-1)

POSITION 3 & 4 (TWO SPEED)
(505SW-2)

POSITION 5 & 6 (SINGLE SPEED)
(505SW-1)

POSITION 7 & 8 (TWO SPEED)
(505SW-2)

1.18
(29.9)
BETWEEN CENTERS

3.52
(89.4)

2.31
(58.7)

NOTES:
1. INSTALLATION INSTRUCTIONS, BUTTON ID. LABELS. ARE PACK WITH THE PART.
2. ALL BUTTONS ARE HIGH AMBIENT, CHEMICALLY RESISTANT MATERIAL - COLOR BLACK

RELEASE DRAWING
EC NO: WNA2009-0803
DRWN: TVICKERS
CHKD: HK
APPR: DTTILUS
REV A

QUALITY SYMBOLS
▽=0
∇=0

GENERAL TOLERANCES (UNLESS SPECIFIED)	
	mm INCH
4 PLACES	±.005 ±.002
3 PLACES	±.010 ±.005
2 PLACES	±.015 ±.007
1 PLACE	±.020 ±.009
ANGULAR ±.5°	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE INCH/(MM)	
DRAWN BY	DATE
TV	2009/06/04
CHECKED BY	DATE
HK	2009/06/04
APPROVED BY	DATE
DT	2009/06/04
MATERIAL NO.	1301260313
SIZE	A

SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
---	---	---
TITLE 5058 W/(2) 505SW-1 &(2) 505SW-2		
MATERIAL NO. 1301260313		
DOCUMENT NO. SD-130126-028		SHEET NO. 1 OF 1
MOLLEX MOLEX INCORPORATED		
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

6 5 4 3 2 1

E

D

C

B

A