

**Bolt-type screw terminals  
WQL 3 WFF35**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com



**Klippon® Connect with stud Technology**

Our stud terminals are an established, robust connection alternative for particularly harsh environments. The extensive accessories and quality workmanship ensure high productivity in planning and installation – and sustainable safety in operation..

**General ordering data**

|            |   |
|------------|---|
| Type       | WQL 3 WFF35   |
| Order No.  | <a href="#">1065400000</a>                                  |
| Version    | Bolt-type screw terminals, Cross-connector, No. of poles: 3 |
| GTIN (EAN) | 4008190065812   |
| Qty.       | 5 pc(s).  |

## Data sheet

### Bolt-type screw terminals WQL 3 WFF35

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 15 mm   | Width (inches)  | 0.591 inch |
| Height     | 69 mm   | Height (inches) | 2.717 inch |
| Depth      | 3 mm    | Depth (inches)  | 0.118 inch |
| Net weight | 23.36 g |                 |            |

### Material data

|          |               |        |      |
|----------|---------------|--------|------|
| Material | Copper - zinc | Colour | Grey |
|----------|---------------|--------|------|

### System specifications

|               |      |
|---------------|------|
| Mounting rail | none |
|---------------|------|

### Additional technical data

|                          |         |                     |                 |
|--------------------------|---------|---------------------|-----------------|
| Explosion-tested version | No      | Installation advice | Direct mounting |
| Type of fixing           | Screwed |                     |                 |

### Dimensions

|                 |       |
|-----------------|-------|
| Pitch in mm (P) | 27 mm |
|-----------------|-------|

### Rating data

|               |       |
|---------------|-------|
| Rated current | 125 A |
|---------------|-------|

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000489    | ETIM 4.0   | EC000489    |
| ETIM 5.0   | EC000489    | ETIM 6.0   | EC000489    |
| UNSPSC     | 30-21-18-01 | eClass 5.1 | 27-14-11-40 |
| eClass 6.2 | 27-14-11-40 | eClass 7.1 | 27-14-11-40 |
| eClass 8.1 | 27-14-11-40 | eClass 9.0 | 27-14-11-40 |
| eClass 9.1 | 27-14-11-40 |            |             |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |  |
|--------------------|--|
| Brochure/Catalogue | <a href="#">CAT 1 TERM 16/17 EN</a>      |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a> |