

**SINGLE-PHASE GLASS PASSIVATED
SILICON BRIDGE RECTIFIER**

VOLTAGE RANGE 50 to 1000 Volts CURRENT 15 Amperes



FEATURES

- * Low leakage
- * Low forward voltage
- * Mounting position : Any
- * Surge overload rating: 150 Amperes peak
- * Ideal for printed circuit boards
- * MSL: Level 1

MECHANICAL DATA

- * Epoxy: Device has UL flammability classification 94V-0

RS-15MLS



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
resistive or inductive load.

MAXIMUM CHARACTERISTICS (@ TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	RS1501MLS	RS1502MLS	RS1503MLS	RS1504MLS	RS1505MLS	RS1506MLS	RS1507MLS	UNITS
Maximum Recurrent Peak Reverse Voltage	VRRM	50	100	200	400	600	800	1000	Volts
Maximum RMS Bridge Input Voltage	VRMS	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	VDC	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Output Current at Tc=100 °C degree with heatsink	Io	15							Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load	IFSM	220							Amps
Typical Current Square Time	I ² T	200							A ² S
Insulation voltage	Viso	3000							Volts
Typical Thermal Resistance from junction to ambient	RθJA	22							°C/W
Typical Thermal Resistance from junction to case	RθJC	1.5							
Operating and Storage Temperature Range	TJ,TSTG	-55 to + 150							°C

ELECTRICAL CHARACTERISTICS (@ TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	RS1501MLS	RS1502MLS	RS1503MLS	RS1504MLS	RS1505MLS	RS1506MLS	RS1507MLS	UNITS	
Maximum Forward Voltage Drop per element at 7.5A DC	VF	1.1							Volts	
Maximum Reverse Current at Rated DC Blocking Voltage per element	IR	@TA=25 °C							0.2	μAmps
		@TA=100 °C							50	μAmps

Note: "Fully ROHS compliant", "100% Sn plating (Pb-free)".

RATING AND CHARACTERISTICS CURVES (RS1501MLS THRU RS1507MLS)




FIG.1 MAXIMUM INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.2 SURGE FORWARD CURRENT CAPABILITY




FIG.3 TYPICAL FORWARD CURRENT DERATING CURVE






FIG.4 MAXIMUM REVERSE CHARACTERISTICS

Marking Description



RS-15MLS



Dimensions in millimeters

Dim	Min	Max
A	15.6	16.2
B	28.7	29.3
C	14.2	14.8
D	1.5	1.7
E	14.6	15.2
F	7.3	7.7
G	0.9	1.1
H	4.3	4.9
I	3.3	3.9
J	3.1	3.4
K	8.7	9.3
L	2.5	2.9
M	0.4	0.6
N	9.8	10.2

PACKAGING OF DIODE AND BRIDGE RECTIFIERS

BULK PACK

PACKAGE	PACKING CODE	EA PER BOX	INNER BOX SIZE (mm)	CARTON SIZE (mm)	EA PER CARTON	GROSS WEIGHT(Kg)
RS-15MLS	-B	250	300*138*35	319*296*165	2000	9.7

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.