

250 V NON/600 V NOS Class K5 and H fuses



Description

Basic protection 250V NON Class K5 and H general purpose, non-current-limiting, one-time fuses.

Catalog symbol

- NON-(amp)

Ratings

- Volts
 - 250 Vac
 - 125 Vdc (1/8-100 A)
- Amps 1/8-600 A
- IR
 - 50 kA Vac RMS Sym. (1/8-60 A)
 - 10 kA Vac RMS Sym. (65-600 A)
 - 50 kA Vdc (1/8-60 A)
 - 10 kA Vdc (65-100 A)

Agency information

- UL Listed, Class K5 (1/8-60 A), Std. 248-9, Class H (65-600 A), Std. 248-6 (125 Vdc 1/8-100 A), UL Guide JDDZ, File E4273
- CSA Certified, Class 1421-01, File 53787 (1/8-12 A, 65-600 A)†
- CE

† For CSA Certified 15-60 A, see PON data sheet no. 4126.

Catalog numbers (amps)


| | | | | |
|------------|------------|--------|---------|---------|
| NON-1/8 | NON-3 | NON-12 | NON-65 | NON-200 |
| NON-1/2 | NON-3-2/10 | NON-15 | NON-70 | NON-225 |
| NON-3/4 | NON-4 | NON-20 | NON-75 | NON-250 |
| NON-8/10 | NON-5 | NON-25 | NON-80 | NON-300 |
| NON-1 | NON-6 | NON-30 | NON-90 | NON-350 |
| NON-1-1/4 | NON-6-1/4 | NON-35 | NON-100 | NON-400 |
| NON-1-1/2 | NON-7 | NON-40 | NON-110 | NON-450 |
| NON-1-6/10 | NON-8 | NON-45 | NON-125 | NON-500 |
| NON-2 | NON-9 | NON-50 | NON-150 | NON-600 |
| NON-2-1/2 | NON-10 | NON-60 | NON-175 | |

Carton quantity

| Amps | Qty. |
|---------|------|
| 1/8-60 | 10 |
| 65-100 | 5 |
| 110-600 | 1 |

Dimensions – in

All Diameters ± 0.008



Features

- Protect lighting, heating and other circuits not subject to temporary surges and where available short-circuit currents are relatively low
- NON one-time fuses do not have any appreciable degree of timedelay and thus should not be specified in circuits where large transients or motor overloads occur. Use Bussmann series advanced protection FUSETRON™ FRN-R or ultimate protection Low-Peak™ LPN-RK dual-element, time-delay fuses.
- For general purpose circuits, size at amp rating of circuit
- For motor circuits, size at 300% to 400% according to the NEC® motor ampacity tables 430.247 to 430.250, per 430.6(A)(1)



Powering Business Worldwide

Recommended fuse blocks


- 1-, 2- and 3-pole modular fuse blocks up to 600 amps — see data sheet no. 10487
- 1-, 2- and 3-pole modular power distribution fuse blocks up to 60 amps — see data sheet no. 10490

Fuse reducers for Class R fuses

| Equipment fuse clips | Desired fuse (case) size | Catalog no. (pairs) 250V |
|----------------------|--------------------------|--------------------------|
| 60 A | 30 A | NO.263 |
| 100 A | 30 A | NO.213 |
| | 60 A | NO.216 |
| 200 A | 60 A | NO.226 |
| | 100 A | NO.2621 |
| 400 A | 100 A | NO.2641† |
| | 200 A | NO.2642 |
| 600 A | 100 A | NO.2661† |
| | 200 A | NO.2662† |
| | 400 A | NO.2664† |

† Not CSA certified.
 For additional information on Class K5 & H fuse reducers, see data sheet no. 1118.

NON time-current curves — average melt





Description

Basic protection 600 V NOS Class K5 and H general purpose, non-current-limiting, one-time fuses.

Catalog symbol

- NOS-(amp)

Ratings

- Volts 600 Vac
- Amps 1-600 A
- IR
 - 50 kA Vac RMS Sym. (1-60 A)
 - 10 kA Vac RMS Sym. (70-600 A)

Agency information

- UL Listed, Class K5 (1-60 A), Std. 248-9, Class H (70-600 A), Std. 248-6, UL Guide JDDZ, File E4273
- CSA Certified, Class 1421-01, File 53787
- CE

Catalog Numbers (amps)


| | | | | |
|-------|--------|--------|---------|---------|
| NOS-1 | NOS-9 | NOS-40 | NOS-100 | NOS-300 |
| NOS-2 | NOS-10 | NOS-45 | NOS-110 | NOS-350 |
| NOS-3 | NOS-12 | NOS-50 | NOS-125 | NOS-400 |
| NOS-4 | NOS-15 | NOS-60 | NOS-150 | NOS-450 |
| NOS-5 | NOS-20 | NOS-70 | NOS-175 | NOS-500 |
| NOS-6 | NOS-25 | NOS-75 | NOS-200 | NOS-600 |
| NOS-7 | NOS-30 | NOS-80 | NOS-225 | |
| NOS-8 | NOS-35 | NOS-90 | NOS-250 | |

Carton Quantity

| Amps | Qty. |
|---------|------|
| 1-60 | 10 |
| 70-100 | 5 |
| 110-600 | 1 |

Dimensions – in

All Diameters ± 0.008



Features

- Protect lighting, heating and other circuits not subject to temporary surges and where available short-circuit currents are relatively low
- NOS one-time fuses do not have any appreciable degree of timedelay and thus should not be specified in circuits where large transients or motor overloads occur. Use Bussmann series advanced protection FUSETRON FRS-R or ultimate protection Low-Peak LPS-RK dual-element, time-delay fuses.
- For general purpose circuits, size at amp rating of circuit
- For motor circuits, size at 300% to 400% according to the NEC® motor ampacity tables 430.247 to 430.250, per 430.6(A)(1)

Recommended fuse blocks

- 1-, 2- and 3-pole modular fuse blocks up to 600 amps — see data sheet no. 10487
- 1-, 2- and 3-pole modular power distribution fuse blocks up to 60 amps — see data sheet no. 10490


Fuse reducers for Class R fuses

| Equipment fuse clips | Desired fuse (case) size | Catalog no. (pairs) 600V |
|----------------------|--------------------------|--------------------------|
| 60 A | 30 A | NO.663 |
| 100 A | 30 A | NO.216 |
| | 60 A | NO.616 |
| 200 A | 60 A | NO.626 |
| | 100 A | NO.2621 |
| 400 A | 100 A | NO.2641† |
| | 200 A | NO.2642 |
| | 100 A | NO.2661† |
| 600 A | 200 A | NO.2662† |
| | 400 A | NO.2664† |

† Not CSA certified.

For additional information on Class R fuse reducers, see data sheet no 1118.

NOS time-current curves — average melt



The only controlled copy of this data sheet is the electronic read-only version located on the Eaton network drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Eaton
 1000 Eaton Boulevard
 Cleveland, OH 44122
 Eaton.com

Bussmann Division
 114 Old State Road
 Ellisville, MO 63021
 United States
 Eaton.com/bussmannseries

© 2017 Eaton
 All Rights Reserved
 Printed in USA
 Publication No. 1030 — BU-SB13738
 June 2017

Eaton, Bussmann, Low-Peak and Fusetron are valuable trademarks of Eaton in the U.S. and other countries. You are not permitted to use the Eaton trademarks without prior written consent of Eaton.

CSA is a registered trademark of the Canadian Standards Group.
 NEC is a registered trademark of the National Fire Protection Association.
 UL is a registered trademark of the Underwriters Laboratories, Inc.

For Eaton's Bussmann series product information, call 1-855-287-7626 or visit: Eaton.com/bussmannseries

Follow us on social media to get the latest product and support information.

