


# 1200V XPT™ IGBT GenX4™

## IXYK140N120A4


Ultra Low-Vsat IGBT for  
up to 5kHz Switching



$V_{CES} = 1200V$   
 $I_{C110} = 140A$   
 $V_{CE(sat)} \leq 1.70V$   
 $t_{fi(typ)} = 320ns$

| Symbol         | Test Conditions  | Maximum Ratings     |            |
|----------------|--|---------------------|------------|
| $V_{CES}$      | $T_J = 25^\circ C$ to $175^\circ C$  | 1200                | V          |
| $V_{CGR}$      | $T_J = 25^\circ C$ to $175^\circ C$ , $R_{GE} = 1M\Omega$                      | 1200                | V          |
| $V_{GES}$      | Continuous   | $\pm 20$            | V          |
| $V_{GEM}$      | Transient  | $\pm 30$            | V          |
| $I_{C25}$      | $T_C = 25^\circ C$ (Chip Capability)   | 480                 | A          |
| $I_{LRMS}$     | Terminal Current Limit   | 160                 | A          |
| $I_{C110}$     | $T_C = 110^\circ C$  | 140                 | A          |
| $I_{CM}$       | $T_C = 25^\circ C$ , 1ms   | 1200                | A          |
| <b>SSOA</b>    | $V_{GE} = 15V$ , $T_{VJ} = 125^\circ C$ , $R_G = 2\Omega$                      | $I_{CM} = 280$      | A          |
| <b>(RBSOA)</b> | Clamped Inductive Load   | $0.8 \cdot V_{CES}$ | V          |
| $P_C$          | $T_C = 25^\circ C$   | 1500                | W          |
| $T_J$          |  | -55 ... +175        | $^\circ C$ |
| $T_{JM}$       |  | 175                 | $^\circ C$ |
| $T_{stg}$      |  | -55 ... +175        | $^\circ C$ |
| $T_L$          | Maximum Lead Temperature for Soldering<br>1.6 mm (0.062 in.) from Case for 10s | 300                 | $^\circ C$ |
| $M_d$          | Mounting Torque  | 1.13/10             | Nm/lb.in   |
| <b>Weight</b>  |  | 10                  | g          |

TO-264  
(IXYK)



G = Gate                      E = Emitter  
C = Collector                Tab = Collector

### Features

- Optimized for Low Conduction Losses
- Positive Thermal Coefficient of  $V_{ce(sat)}$
- International Standard Package

### Advantages

- High Power Density
- Low Gate Drive Requirement

### Applications

- Power Inverters
- UPS
- Motor Drives
- SMPS
- PFC Circuits
- Battery Chargers
- Welding Machines
- Lamp Ballasts
- Inrush Current Protection Circuits

| Symbol        | Test Conditions<br>( $T_J = 25^\circ C$ , Unless Otherwise Specified) | Characteristic Values |              |                    |
|---------------|---|-----------------------|--------------|--------------------|
|               |   | Min.                  | Typ.         | Max.               |
| $BV_{CES}$    | $I_C = 250\mu A$ , $V_{GE} = 0V$                                      | 1200                  |              | V                  |
| $V_{GE(th)}$  | $I_C = 4mA$ , $V_{CE} = V_{GE}$                                       | 4.5                   |              | 6.5 V              |
| $I_{CES}$     | $V_{CE} = V_{CES}$ , $V_{GE} = 0V$<br>$T_J = 125^\circ C$             |                       |              | 25 $\mu A$<br>5 mA |
| $I_{GES}$     | $V_{CE} = 0V$ , $V_{GE} = \pm 20V$                                    |                       |              | $\pm 200$ nA       |
| $V_{CE(sat)}$ | $I_C = I_{C110}$ , $V_{GE} = 15V$ , Note 1<br>$T_J = 150^\circ C$     |                       | 1.34<br>1.50 | 1.70 V<br>V        |

| Symbol Test Conditions<br>( $T_J = 25^\circ\text{C}$ Unless Otherwise Specified) |   | Characteristic Values |      |                    |
|--|---|-----------------------|------|--------------------|
|  |   | Min.                  | Typ. | Max.               |
| $g_{fs}$   | $I_C = 60\text{A}, V_{CE} = 10\text{V}, \text{Note 1}$  | 60                    | 100  | S                  |
| $C_{ies}$  | $V_{CE} = 25\text{V}, V_{GE} = 0\text{V}, f = 1\text{MHz}$  |                       | 8300 | pF                 |
| $C_{oes}$  |   |                       | 470  | pF                 |
| $C_{res}$  |   |                       | 300  | pF                 |
| $Q_{g(on)}$  | $I_C = I_{C110}, V_{GE} = 15\text{V}, V_{CE} = 0.5 \cdot V_{CES}$   |                       | 420  | nC                 |
| $Q_{ge}$   |   |                       | 68   | nC                 |
| $Q_{gc}$   |   |                       | 210  | nC                 |
| $t_{d(on)}$  | <b>Inductive load, <math>T_J = 25^\circ\text{C}</math></b><br>$I_C = 70\text{A}, V_{GE} = 15\text{V}$<br>$V_{CE} = 0.5 \cdot V_{CES}, R_G = 1.5\Omega$<br>Note 2  |                       | 52   | ns                 |
| $t_{ri}$   |   |                       | 47   | ns                 |
| $E_{on}$   |   |                       | 4.9  | mJ                 |
| $t_{d(off)}$   |   |                       | 590  | ns                 |
| $t_{fi}$   |   |                       | 320  | ns                 |
| $E_{off}$  |   |                       | 12.0 | mJ                 |
| $t_{d(on)}$  | <b>Inductive load, <math>T_J = 150^\circ\text{C}</math></b><br>$I_C = 70\text{A}, V_{GE} = 15\text{V}$<br>$V_{CE} = 0.5 \cdot V_{CES}, R_G = 1.5\Omega$<br>Note 2 |                       | 44   | ns                 |
| $t_{ri}$   |   |                       | 42   | ns                 |
| $E_{on}$   |   |                       | 7.4  | mJ                 |
| $t_{d(off)}$   |   |                       | 710  | ns                 |
| $t_{fi}$   |   |                       | 530  | ns                 |
| $E_{off}$  |   |                       | 20.0 | mJ                 |
| $R_{thJC}$   |   |                       | 0.10 | $^\circ\text{C/W}$ |
| $R_{thCS}$   |   | 0.15                  |      | $^\circ\text{C/W}$ |


**Notes:**

1. Pulse test,  $t \leq 300\mu\text{s}$ , duty cycle,  $d \leq 2\%$ .
2. Switching times & energy losses may increase for higher  $V_{CE}$  (clamp),  $T_J$  or  $R_G$ .


Littelfuse reserves the right to change limits, test conditions and dimensions.

|   |           |           |           |           |              |              |              |              |              |             |
|---|-----------|-----------|-----------|-----------|--------------|--------------|--------------|--------------|--------------|-------------|
| IXYS MOSFETs and IGBTs are covered            | 4,835,592 | 4,931,844 | 5,049,961 | 5,237,481 | 6,162,665    | 6,404,065 B1 | 6,683,344    | 6,727,585    | 7,005,734 B2 | 7,157,338B2 |
| by one or more of the following U.S. patents: | 4,860,072 | 5,017,508 | 5,063,307 | 5,381,025 | 6,259,123 B1 | 6,534,343    | 6,710,405 B2 | 6,759,692    | 7,063,975 B2 |             |
|   | 4,881,106 | 5,034,796 | 5,187,117 | 5,486,715 | 6,306,728 B1 | 6,583,505    | 6,710,463    | 6,771,478 B2 | 7,071,537    |             |


**Fig. 1. Output Characteristics @  $T_J = 25^\circ\text{C}$**




**Fig. 2. Extended Output Characteristics @  $T_J = 25^\circ\text{C}$**




**Fig. 3. Output Characteristics @  $T_J = 150^\circ\text{C}$**




**Fig. 4. Dependence of  $V_{CE(sat)}$  on Junction Temperature**




**Fig. 5. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage**




**Fig. 6. Input Admittance**




**Fig. 7. Transconductance**




**Fig. 8. Gate Charge**




**Fig. 9. Capacitance**









**Fig. 10. Reverse-Bias Safe Operating Area**




**Fig. 11. Maximum Transient Thermal Impedance**




**Fig. 12. Inductive Switching Energy Loss vs. Collector Current**

**Fig. 13. Inductive Switching Energy Loss vs. Collector-Emitter Voltage**

**Fig. 14. Inductive Switching Energy Loss vs. Gate Resistance**

**Fig. 15. Inductive Switching Energy Loss vs. Junction Temperature**

**Fig. 16. Inductive Turn-off Switching Times vs. Gate Resistance**

**Fig. 17. Inductive Turn-off Switching Times vs. Collector Current**



**Fig. 18. Inductive Turn-off Switching Times vs. Junction Temperature**




**Fig. 19. Inductive Turn-on Switching Times vs. Gate Resistance**




**Fig. 20. Inductive Turn-on Switching Times vs. Collector Current**



**Fig. 21. Inductive Turn-on Switching Times vs. Junction Temperature**



**TO-264 Outline**


| SYMBOL | INCHES  |       | MILLIMETERS |       |
|--------|---------|-------|-------------|-------|
|        | MIN     | MAX   | MIN         | MAX   |
| A      | .185    | .209  | 4.70        | 5.31  |
| A1     | .102    | .118  | 2.59        | 3.00  |
| b      | .037    | .055  | 0.94        | 1.40  |
| b1     | .087    | .102  | 2.21        | 2.59  |
| b2     | .110    | .126  | 2.79        | 3.20  |
| c      | .017    | .029  | 0.43        | 0.74  |
| D      | 1.007   | 1.047 | 25.58       | 26.59 |
| E      | .760    | .799  | 19.30       | 20.29 |
| e      | .215BSC |       | 5.46 BSC    |       |
| J      | .000    | .010  | 0.00        | 0.25  |
| K      | .000    | .010  | 0.00        | 0.25  |
| L      | .779    | .842  | 19.79       | 21.39 |
| L1     | .087    | .102  | 2.21        | 2.59  |
| øP     | .122    | .138  | 3.10        | 3.51  |
| øP1    | .270    | .290  | 6.86        | 7.37  |
| Q      | .240    | .256  | 6.10        | 6.50  |
| Q1     | .330    | .346  | 8.38        | 8.79  |
| øR     | .155    | .187  | 3.94        | 4.75  |
| øR1    | .085    | .093  | 2.16        | 2.36  |
| S      | .243    | .253  | 6.17        | 6.43  |



---

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).

Littelfuse reserves the right to change limits, test conditions and dimensions.

---