


PROPRIETARY INFORMATION:
 PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR
 USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY
 PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.


REVISION		DATE	APPROVED
REV	DESCRIPTION		
A	INITIAL RELEASE, RFS. 15679,BS	02/20/09	BS



GENERAL SPECIFICATIONS:

RATING: 16A / 125V AC
 CABLE TYPE / SIZE: SJTW, 14 AWG x 3C
 TEMPERATURE RATING: 105° C
 CONDUCTOR COLORS: BLACK / WHITE / GREEN
 CABLE JACKET COLOR: BLACK
 OVERALL LENGTH (L): 3660 ± 50 mm
 CABLE OUTER DIAMETER: 9.3 ± 0.2 mm
 END 'A' TERMINATION: NEMA 5-20P, RIGHT ANGLE
 END 'B' TERMINATION: IEC 320 /C19, RIGHT ANGLE
 APPROVALS PLUG: UL, CSA or cUL
 APPROVALS CABLE: UL, CSA or cUL
 APPROVALS CONNECTOR: UL, CSA or cUL

**PACKING:
 HANKING**



NOTES:

1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVALS SYMBOLS OR FILE NUMBER(S).



DASH NO.	PART NO	REV.	DESCRIPTION	NOTES
TABULATION BLOCK				
			TOLERANCES: DECIMALS ANGULAR .xx +/- 0.1 +/- 1° .xxx +/- .005	GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111 www.globtek.com
			MILLIMETERS ANGULAR .xx +/- 0.3 +/- 1° .xxx +/- .013	
INIT.BY: BS	DATE: 05/27/08	DWG TITLE: NORTH AMERICAN DETACHABLE CORDSET		
DRAWN: NF	DATE: 05/27/08	FSCN No.: G, CC, YL	SIZE A	MODEL: N / A
APRVD: HM	DATE: 05/27/08	SCALE: NONE	PART NO: 37512312F7032L(R)	
				REV. A
				SHEET 1/1

Foot Note:
 Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

Limitation of Use:
 Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

Contents of this document are subject to change without prior notice