



**Metric table**

Dimensions in: millimeters - inches

<sup>1</sup> d <sub>1</sub>	<sup>2</sup> d <sub>2</sub> Thread EN 530			<sup>2</sup> d <sub>2</sub> Thread EN 530.5	d <sub>3</sub>	h	k	t min.
15 0.59	M 3	M 4	M 5	M 5	11 0.43	11 0.43	9 0.35	6 0.24
18 0.71	M 5	-	-	-	13 0.51	12 0.47	9 0.35	5 0.20
22 0.87	M 6	-	-	M 6	15 0.59	14 0.55	10 0.39	6 0.24
25 0.98	M 6	-	-	M 6	19 0.75	18 0.71	12 0.47	10 0.39
30 1.18	M 8	-	-	M 8	24 0.94	18 0.71	12 0.47	10 0.39
40 1.57	M 10	-	-	-	29 1.14	26 1.02	16 0.63	13 0.51
50 1.97	M 10	M 12	-	-	36 1.42	32 1.26	20 0.79	20 0.79

**Specification**

- Knurled nut  
Plastic  
Duroplast (Phenolic PF)  
- Temperature resistant up to 230 °F (110 °C)  
- Black, shiny finish
- **EN 530**  
Tapped insert  
Brass
- **EN 530.5**  
Tapped insert  
Stainless steel AISI 303
- *Plastic Characteristics* → page 2135
- *Stainless Steel Characteristics* → page 2143
- [RoHS compliant](#)

**On request**

- With tapped through bore (brass insert)

**Information**

The surface quality of EN 530 and EN 530.5 knurled nuts is of a sufficiently high standard to meet the highest requirements. Flash marks are not visible.  
Duroplast material is highly resistant to chemicals.

How to order (Brass insert) <sup>1</sup> <sup>2</sup> <b>EN 530-40-M10</b>	1	Handle diameter d <sub>1</sub>
	2	Thread d <sub>2</sub>
How to order (Stainless steel insert) <sup>1</sup> <sup>2</sup> <b>EN 530.5-22-M6</b>	1	Handle diameter d <sub>1</sub>
	2	Thread d <sub>2</sub>