

Aug. 1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	VOLTAGE		APPLICABLE CABLE	⚠ CABLE DIAMETER : φ6.6~7.6	
	CURRENT				
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.			X	X
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
⚠	2	DIS-E-00003216	KN. ICHIKAWA	TU. TANIGUCHI	20201019
REMARK			APPROVED	AO. SUZUKI	20090511
THIS PRODUCT SHALL BE MATED WITH DH30B-27S, IT APPLIES TO DH30B-27S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS.			CHECKED	KN. ICHIKAWA	20090511
			DESIGNED	MO. SHIMOYAMA	20090511
			DRAWN	MO. SHIMOYAMA	20090511
Unless otherwise specified, refer to IEC 60512. ⚠					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-126947-00	
HRS	SPECIFICATION SHEET		PART NO.	DH-27-CT2B	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0048-8-00	⚠ 1/1