

"High Frequency Ceramic Solutions"

5.5 GHz Band Pass Filter

Detail Specification

P/N 5487BP15B675



Rev. 01/29/2002 Page 1 of 2

Part Number	Frequency (MHz)	Insertion Loss	Attenuation (min.)	Return Loss	Ripple
5487BP15B675_	5150 - 5825	1.8 dB max	35 dB @ 2.57-2.90 GHz 22 dB @ 10.3-11.65 GHz 30 dB @ 15.45-17.47 GHz	9.5 dB min.	0.7 dB max.

Input Power	Group Delay	Impedance	Operating Temperature Range
3 Watts max	5.0 nS max.	50 Ω	-40 to +85°C


Mechanical Dimensions

	L	W	T	a	b	c	g	p
Inches	0.079 ± .004	0.049 ± .004	0.034 ± .004	0.012 ± .004	0.008 ± .004	0.012 + .004/-0.008	0.014 ± .004	0.026 ± .002
mm	2.0 ± 0.1	1.25 ± 0.1	0.85 ± 0.1	0.30 ± 0.1	0.20 ± 0.1	0.30+0.1/-0.2	0.35 ± 0.1	0.65 ± 0.05




Terminal Configuration

1	GND	4	GND
2	GND	5	GND
3	I/O	6	I/O



Mounting Considerations

Mount these devices with brown colored side facing up. * Line width should be designed to provide 50 Ω impedance matching characteristics.



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.

“High Frequency Ceramic Solutions”


5.5 GHz Band Pass Filter

Detail Specification

P/N 5487BP15B675

Rev. 01/29/2002 Page 2 of 2

Typical Insertion Loss / Return Loss



Delivery

Packaged in embossed tape on 7" reels (3000 / reel)
Standard delivery is eight weeks or sooner ARO