


# GRACE INERTIA 2.0 TE Internal #: 1971030-8 Rectangular Connector Housings, Wire-to-Board, 8 Position, .079 in [2 mm] Centerline, 1 Row, Nylon 66 GF, Plug, Socket, GRACE INERTIA 2.0

#### View on TE.com >

Connectors > Rectangular Connectors > Rectangular Connector Housings > STD Temp Sig GRACE INERTIA Plug



Connector System: Wire-to-Board

Number of Positions: 8

Centerline (Pitch): 2 mm [.079 in ]

Number of Rows: 1

Housing Material: Nylon 66 GF

#### All STD Temp Sig GRACE INERTIA Plug (63)

**TE** 

# Features

### **Product Type Features**

Connector System	Wire-to-Board							
Connector & Housing Type	Plug							
Sealable	No							
Connector & Contact Terminates To	Wire & Cable							
Configuration Features								
Number of Cavities	8							
Number of Positions	8							
Number of Rows	1							
Electrical Characteristics								
Operating Voltage	50 VAC							
Contact Features								
Contact Layout	Inline							

Rectangular Connector Housings, Wire-to-Board, 8 Position, .079 in [2 mm] Centerline, 1 Row, Nylon 66 GF, Plug, Socket, GRACE INERTIA 2.0



Contact Type	Socket
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Color	Natural
Centerline (Pitch)	2 mm[.079 in]
Housing Material	Nylon 66 GF
Dimensions	
Connector Height	7.9 mm[.311 in]
Product Width	6.75 mm[.266 in]
Product Length	17.2 mm[.677 in]
Usage Conditions	
Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
Operation/Application	
Halogen Free	No
Circuit Application	Signal
Identification Marking	
Circuit Identification Feature	Without
Industry Standards	
Agency/Standard	UL
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	200
Packaging Method	Package
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)

Rectangular Connector Housings, Wire-to-Board, 8 Position, .079 in [2 mm] Centerline, 1 Row, Nylon 66 GF, Plug, Socket, GRACE INERTIA 2.0



Candidate List Declared Against: JUNE<br/>2023 (235)<br/>Does not contain REACH SVHCNot Low Halogen - contains Br or Cl > 900<br/>ppm.

Not applicable for solder process capability

Halogen Content

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**




# Also in the Series | GRACE INERTIA 2.0

PCB Headers & Receptacles(70)	Rectangular Connector Housings(20)	Standard Rectangular Connectors(18)	Wire-to-Board Connector Assemblies & Housings(1)

Rectangular Connector Housings, Wire-to-Board, 8 Position, .079 in [2 mm] Centerline, 1 Row, Nylon 66 GF, Plug, Socket, GRACE INERTIA 2.0





# Customers Also Bought



250 FASTON FLAG REC 12-10 AWG	250 PL EX REC. 22-18AWG PTBR	250 PL EX REC. 18-14AWG PTBR	187 FASTON, FLAG, REC., 16-20 AWG,
TPBR			TPBR

### Documents

Product Drawings

8POS Plug Housing for GIC 2.0 EV Series

English

### CAD Files

3D PDF

3D

Customer View Model

#### ENG\_CVM\_CVM\_1971030-8\_F\_c-1971030-8-f.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_1971030-8\_F\_c-1971030-8-f.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1971030-8\_F\_c-1971030-8-f.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Rectangular Connector Housings, Wire-to-Board, 8 Position, .079 in [2 mm] Centerline, 1 Row, Nylon 66 GF, Plug, Socket, GRACE INERTIA 2.0



Product Specifications Application Specification

English