### K21F1C-P05NJG0-550S

# series\_f, type\_k2



#### **General information**

| Part number       | K21F1C-P05NJG0-550S |  |
|-------------------|---------------------|--|
| Termination       | crimp               |  |
| Size              | 1                   |  |
| Locking principle | break, push         |  |
| Coding            | 1_halfshell         |  |
| Cable Diameter    | cable_mini_55       |  |
| Cable outlet      | bend_relief         |  |





# **Contact insert description**

| Number of contacts | 5         |
|--------------------|-----------|
| Contact type       | sockets   |
| Contact diameter   | 09mm      |
| Insulator material | peek      |
| Wire cross section | 22-26_awg |
| Termination        | crimp     |

 $reverse\_gender\_on\_request$ 

#### **Technical information**

| Max. creepage and air clearance distance | 10_mm     | 07 <sub>_mm</sub> |
|--|-----------|-------------------|
| Nominal current single contact           | 075_a     | iec_60512_5_2     |
| Nominal current insert                   | 5,625 A   | vde_0298_4        |
| Test voltage                             | 135_kv_ac | sae_13441         |

safety\_text

### Mechanical and environmental data

| Degree of protection* | ip50     |
|-----------------------|----------|
| Operating temperature | 40_120_c |
| Mating cycles         | 5000     |

 $mated\_unmated$ 

# Material and surface treatments

| Housing | m_chrome      |
|---------|---------------|
| Contact | cu_alloy_gold |
|         |               |

safety\_text\_2 ul\_text illustrative\_text