### Economy Power 2.5

TE Internal #: 2132415-3

PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 2.5 mm [. 098 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder,


Economy Power 2.5


View on TE.com >



### Connectors > PCB Connectors > PCB Headers & Receptacles











Connector System: Wire-to-Board

Number of Positions: 3

Number of Rows: 1

Centerline (Pitch): 2.5 mm [ .098 in ]
PCB Mount Orientation: Vertical

### **Features**

### **Product Type Features**

| Connector System                  | Wire-to-Board         |
|-----------------------------------|-----------------------|
| Header Type                       | Fully Shrouded        |
| Sealable                          | No                    |
| Connector & Contact Terminates To | Printed Circuit Board |
| PCB Connector Assembly Type       | PCB Mount Header      |

### **Configuration Features**

| Connector Contact Load Condition | Fully Loaded |
|----------------------------------|--------------|
| Number of Positions              | 3            |
| Number of Rows                   | 1            |
| PCB Mount Orientation            | Vertical     |

### **Electrical Characteristics**

| Operating Voltage | 250 VAC |
|-------------------|---------|
|                   |         |

### **Body Features**

| Primary Product Color | Natural |  |
|-----------------------|---------|--|



| Contact Features  |                        |
|---|------------------------|
| Contact Mating Area Length                              | 3.6 mm[.142 in]        |
| PCB Contact Termination Area Plating Material Thickness | 2.032 μm[80 μin]       |
| Contact Layout  | Inline                 |
| Mating Pin Diameter                                     | .6 mm[.024 in]         |
| Contact Mating Area Plating Material Thickness          | 2 – 5 μm[80 – 200 μin] |
| Contact Shape & Form                                    | Round                  |
| Contact Mating Area Plating Material Finish             | Bright                 |
| PCB Contact Termination Area Plating Material           | Tin                    |
| Contact Base Material                                   | Brass                  |
| Contact Mating Area Plating Material                    | Tin                    |
| Contact Type  | Pin                    |
| Contact Current Rating (Max)                            | 4.2 A                  |
| ermination Features                                     |                        |
| Round Termination Post & Tail Diameter                  | .6 mm[.024 in]         |
| Termination Post & Tail Length                          | 3.4 mm[.134 in]        |
| Termination Method to Printed Circuit Board             | Through Hole - Solder  |
| Mechanical Attachment                                   |                        |
| Mating Alignment Type                                   | Polarization           |
| Mating Retention  | With                   |
| PCB Mount Retention Type                                | Kinked                 |
| Mating Retention Type                                   | Latch                  |
| Connector Mounting Type                                 | Board Mount            |
| Mating Alignment  | With                   |
| PCB Mount Alignment                                     | Without                |
| PCB Mount Retention                                     | With                   |
| Housing Features  |                        |
| Housing Material  | PBT GF                 |
| Centerline (Pitch)                                      | 2.5 mm[.098 in]        |
| Dimensions  |                        |
| Connector Length  | 12.5 mm[.49 in]        |
| Connector Height  | 8.8 mm[.346 in]        |



| Connector Width             | 6.4 mm[.252 in]               |
|-----------------------------|-------------------------------|
| PCB Thickness (Recommended) | 1.6 mm[.063 in]               |
| Usage Conditions            |                               |
| Operating Temperature Range | -55 – 105 °C[-67 – 221 °F]    |
| Operation/Application       |                               |
| Circuit Application         | Power & Signal                |
| Industry Standards          |                               |
| Glow Wire Rating            | Standard Part - Not Glow Wire |
| UL Flammability Rating      | UL 94V-0                      |
| Packaging Features          |                               |
| Packaging Quantity          | 600                           |

Bag

### **Product Compliance**

Packaging Type

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant  |
|---|--|
| EU ELV Directive 2000/53/EC                   | Compliant  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold  |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUL 2021 (219) Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.   |
| Solder Process Capability                     | Wave solder capable to 265°C   |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



# Compatible Parts








# Also in the Series | Economy Power 2.5



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(494)



PCB Latches, Locks & Retainers(49)



Rectangular Power Connectors(43)



Wire-to-Board Connector Assemblies & Housings(311)



Wire-to-Board Connector Contacts(6)

# Customers Also Bought



TE Part #2132415-6 EP2.5 Shrouded HDR ASSY 6P VERT w /o boss



TE Part #1-1969442-4
EP 2.5 TPA Housing, 14 Pos



TE Part #1721083-5 OJ-SS-109LMHF,000



TE Part #1-1969582-0 ASSY, HDR, VERT, NO-BOSS, DUAL ROW,EP2.5











EP 11P HEADER ASY NO 6,10 PINS

TE Part #1744439-5 EP2.5 Shrd HDR ASSY 5P VERT, GW TE Part #2132415-7
EP2.5 Shrouded HDR ASSY 7P VERT w
/o boss



### **Documents**

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2132415-3\_G.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2132415-3\_G.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2132415-3\_G.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

7-1773458-5\_ECONOMY\_POWER\_QRG

English

7-1773461-6\_EP2.5\_Connector\_Series

English

## **Product Specifications**

**Application Specification** 

English

### **Product Environmental Compliance**

**Product Compliance Document** 

English

PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 2.5 mm [.098 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, Economy Power 2.5



## Product Compliance Document

English

Agency Approvals

**UL Report** 

English

**UL Report** 

English