



RECOMMENDED MOUNTING HOLE DIMENSIONS (P.C.B.)

NOTES:
1. CAPTURED CENTER CONTACT

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₀	RELEASED	9/22/89	<i>D. Comella</i>

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
O-RING	FLUROSILICONE 60 (DUROMETER) PER MIL-P-25988, CLASS 1, TYPE 1	N/A

COMPONENT	MATERIAL	FINISH
-----------	----------	--------

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ± .005 ± 1°	DRAWN BY	BB	DATE	9/21/89	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	CHECKED BY	L.ROSS	DATE	9/22/89	
	APPD BY	<i>D. Comella</i>	DATE	9/22/89	

These drawings and specifications are the property of AMP Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	TITLE			AMP
	NO. AP. <u>N/A</u>	OSSP PRINTED CIRCUIT BOARD STRAIGHT PLUG RECEPTACLE STRAIGHT TERMINAL			
		SIZE	CODE IDENT NO.	REV	
		B	26805	4763-0000-00	01 ₀
		SCALE			SHEET 1 OF 1

CUSTOMER DRAWING

AMP PART # 1059919-1
SHEET 1 OF 1 REV B
PER EC # OU20-0261-01