


10-Port USB Hub with Power Supply and International Plug Adapters

MODEL NUMBER: U223-010-INT



Adds 10 USB-A ports to your laptop or computer for connecting printers, hard drives, keyboard/mice and other USB peripherals.

Features

USB 2.0 Hub Adds up to 10 USB Devices to Your Computer or Laptop

This USB hub with a sturdy plastic housing connects 10 USB devices, such as external hard drives, printers, keyboards/mice, MP3 players and barcode scanners, to your PC, laptop or other device with a USB-A port. The hub supports USB 2.0 data transfer rates up to 480 Mbps and is backward compatible with USB 1.1 devices. It provides easy-to-access USB ports to computers stored in cabinets, behind furniture or other hard-to-reach locations.

Plug-and-Play Hub Is Convenient to Use All Over the World

The U223-010-INT requires no software to download and install. It connects to a host computer with the included USB-A to USB-B cable and draws power through the included external power supply. A blue LED indicates the unit is receiving power. Four included international plug adapters (North America, United Kingdom, Europe and Australia) ensure you can use this hub almost anywhere.

Highlights

- Supports USB 2.0 speeds up to 480 Mbps to ensure reliable data transfers
- International plug adapters allow connection to AC power all over the world
- Blue LED indicates the hub is receiving power from the included supply
- Compatible with most recent Windows and macOS versions
- Plug-and-play operation with no software required for easy, immediate installation

System Requirements

Compatible with Windows 98SE, Vista, XP, Me, Win2000, 7, 8, 10 and 11; Mac OS X 10.8 Mountain Lion and macOS Big Sur

Package Includes

- U223-010-INT 10-Port USB 2.0 Hub
- USB Mini-B to USB-A cable (M/M)
- External power supply (Input: 100–240V, 50/60 Hz, 1.5A; Output: 5V 4A)
- (4) International plug adapters (North America, U.K., Europe, Australia)

Specifications

| OVERVIEW | |
|------------------------------|----------------------|
| UPC Code | 037332269713 |
| Product Type | Hub |
| Technology | USB 2.0 (High Speed) |
| Host Connector | USB A (MALE) |
| VIDEO | |
| Number of Monitors Supported | 0 |
| Video Ports | USB A (MALE) |

| DATA | |
|--|--|
| Data Ports | (10) USB A (FEMALE) |
| NETWORK | |
| Network Ports | USB A (FEMALE) |
| INPUT | |
| AC Power Adapter Plug(s) | AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America |
| AC Power Adapter Input Specs (V / Hz / A) | 100-240V / 50/60Hz / 1.5A |
| AC Power Adapter Output Specs (V / A) | 5V / 4A |
| AC Power Adapter Cord Length (ft.) | 5 |
| AC Power Adapter Cord Length (m) | 1.5 |
| Voltage Compatibility (VAC) | 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 |
| Input Plug Type | AS/NZS 3112; BS1363; NEMA 1-15P; Schuko |
| Input Plug Type Details | See POWER: AC Power Adapter specifications |
| Bus Powered | No |
| POWER | |
| Power Source Type | AC Adapter |
| AC Adapter | Input: 100-240V, 50/60Hz, 1.5A; Output: 5V, 4A, 5 ft. |
| DC Barrel Plug | OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | Blue (Power) |
| PHYSICAL | |
| Color | Black |
| Material of Construction | ABS |
| Unit Dimensions (hwd / in.) | 8.712 x 1.311 x 0.629 |
| Unit Dimensions (hwd / cm) | 22.21 x 3.33 x 1.6 |
| Unit Packaging Type | Box |
| Unit Weight (lbs.) | 0.189 |
| Unit Weight (kg) | 0.09 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32° to 113°F (0° to 45°C) |

| | |
|---------------------------------------|--|
| Storage Temperature Range | 14° to 176°F (-10° to 80°C) |
| Operating Humidity Range | 10 to 85% RH, Non-Condensing |
| Storage Humidity Range | 5 to 90% RH, Non-Condensing |
| Power Provided to Connected Device(s) | 500mA from the USB 2.0 computer port is shared between the hub ports |
| CONNECTIONS | |
| Number of Ports | 10 |
| Side A - Connector 1 | USB MINI-B 5-PIN (FEMALE) |
| Side B - Connector 1 | (10) USB A (FEMALE) |
| Connector Plating | Nickel |
| FEATURES & SPECIFICATIONS | |
| USB Specification | USB 2.0 (up to 480 Mbps) |
| Driver Required | No |
| STANDARDS & COMPLIANCE | |
| External Power Supply Certifications | BSMI; C-Tick; CCC; CE; DOE; GS; RoHS; TUV; UL; WEEE |
| Product Certifications | NOM (Mexico) |
| Product Compliance | RoHS; CE (Europe); REACH; WEEE; FCC (USA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |