



## Main

|                                 |                         |
|---------------------------------|-------------------------|
| Range of Product                | Harmony 9001SK          |
| Product or Component Type       | Illuminated push-button |
| Device short name               | 9001SK                  |
| Type of operator                | Spring return           |
| Operator profile                | Green flush, unmarked   |
| Operator additional information | Full guard in plastic   |
| Light block supply              | Direct 120 V AC/DC      |

## Complementary

|   |   |
|---|---|
| Bezel material                              | Plastic   |
| Mounting diameter                           | 1.18 in (30 mm)   |
| Light source                                | Green LED   |
| Bulb base                                   | BA 9s   |
| [Us] rated supply voltage                   | 120 V AC/DC   |
| Contacts type and composition               | 1 NO  |
| Connections - terminals                     | Screw clamp terminals 1 x 0.22...2 x 1.5 mm <sup>2</sup> EN/IEC 60947-1   |
| Tightening torque                           | 7.08 lbf.in (0.8 N.m) EN/IEC 60947-1  |
| Shape of screw head                         | Cross slotted   |
| Mechanical durability                       | 5000000 cycles  |
| Operating position                          | Any position  |
| [Ie] rated operational current              | 0.55 A 125 V, DC-13, A600-Q600 NEMA   |
| [Ui] rated insulation voltage               | 250 V 3)EN/IEC 60947-1  |
| [Uimp] rated impulse withstand voltage      | 2.5 kV EN/IEC 60947-1   |
| Contacts material                           | Silver alloy contacts   |
| Contact operation                           | Standard  |
| Positive opening                            | Without   |
| Short-circuit protection                    | 10 A cartridge fuse EN/IEC 60947-5-1  |
| [Ith] conventional free air thermal current | 10 A  |
| [Icm] rated short-circuit making capacity   | 0.1 KA 240 V DC-13, 7200 VA<br>15 KA 480 V AC-15, 7200 VA<br>30 KA 240 V AC-15, 7200 VA<br>60 KA 120 V AC-15, 7200 VA<br>0.27 KA 250 V DC-13<br>0.55 KA 125 V DC-13<br>0.1 KA 600 V DC-13 |
| Rated breaking capacity                     | 1.2 KA 600 V AC-15, 720 VA<br>1.5 KA 480 V AC-15, 720 VA<br>3 KA 240 V AC-15, 720 VA<br>6 KA 120 V AC-15, 720 VA<br>0.27 KA 250 V DC-13<br>0.55 KA 125 V DC-13<br>0.1 KA 600 V DC-13      |
| Net Weight                                  | 0.40 lb(US) (0.181 kg)  |
| Device presentation                         | Complete product  |

## Environment

|                                       |  |
|---------------------------------------|--|
| Standards                             | JIS C 852<br>CSA C22.2 No 14<br>EN/IEC 60947-1<br>JIS C 4520<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>UL 508 |
| Product Certifications                | UL 508<br>NEMA   |
| Protective treatment                  | TC   |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)   |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)   |
| Vibration resistance                  | 7 gn 2...500 Hz)IEC 60068-2-6  |
| Shock resistance                      | 50 gn IEC 60068-2-27   |
| Electrical shock protection class     | Class II IEC 61140   |
| IP degree of protection               | IP66 IEC 60529   |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 4X                               |

## Ordering and shipping details

|                       |                     |
|-----------------------|---------------------|
| Category              | 21429 - 9001 SK,SKY |
| Discount Schedule     | CS1                 |
| GTIN                  | 3389119070027       |
| Nbr. of units in pkg. | 1                   |
| Package weight(Lbs)   | 6.40 oz (181.437 g) |
| Returnability         | No                  |
| Country of origin     | MX                  |

## Packing Units

|                        |                      |
|------------------------|----------------------|
| Unit Type of Package 1 | PCE                  |
| Package 1 Height       | 5.08 in (12.903 cm)  |
| Package 1 width        | 2.00 in (5.08 cm)    |
| Package 1 Length       | 12.90 in (32.774 cm) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           |  <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information |  Yes   |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

## Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---