




File: E209153



ISO9001:2008 Certified

**Mechanical Specifications (mm)**

	D:	22.0	± max
	T:	6.0	± max
	Lead Diameter	1.0	± nom
	S:	7.8	± nom
	L:	38.0	± nom
	Coating Lead Run Down (straight Leads)	5.0	± max
	B:	11.50	± nom
	C:	3.65	± nom



**Electrical Specifications**

	Resistance:	2.5	Ω	± 20 %
Max Steady State Current upto 65°C:	15.00	A		
Max Rec. Energy Rating:	90	J		
Actual Failure Instantaneous Energy:	200	J		
Maximum Capacitance @ 120 VAC:	6,000	µf		
Maximum Capacitance @ 240 VAC:	1,400	µf		
Resistance @ 100% Max Current:	0.03	Ω		
Resistance @ 50% Max Current:	0.07	Ω		
Body Temperature at 100% Max Current:	172.00	°c		
Dissipation Constant:	32.4	mw/°c		
Thermal Time Constant:	94	Sec.		
Material Type (for Beta and Curve):	H			

<b>SL22 2R515</b>	
Date: 11/11/2008	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: a