

1 2 3 4 5 6 7

A

2.54±0.10

B

5.00±0.15

1.70

Ⓢ3.8

Ⓢ5.0

C

Ⓢ2.45±0.15

A

Ⓢ6.00±0.15

Ⓢ13.60

D

5.40

NOTES:

1. Insulation: Nylon 66, UL94V-0
2. Contact : Brass
- ⑧⑥ 3. Plated: Gold Flash or Tin over Nickel
4. Current Rating: 3A Max
5. Dielectric Voltage: 1000V rms / 1 minute
6. Insulation Resistance: 1000M ohm Min.
7. Contact Resistance: 30m ohm Max.
8. Operating and Storage Temperature: -40°C ~ +105°C
- ③ 9. Mating Cycles: 10 Min.

⑧⑤ AKSPLTx xx

Color:  
RED  
BLACK

Contact Area Plating:  
G: Gold Flash  
Z: Tin plated

E

F

1.20

G

**RoHS compliant**  
Unit:mm

Scale	Free	⑧	Update the dimension and tolerance	25.07.2022	Peter	Date	Name	Description. Jumper Connector	
⑧TOLERANCE		⑦	Change the plant	20.04.2022	Winnie	Drawn	21.03.2007		Hellwig
X.	±0.35	⑥	Update plated information	20.08.2015	Ray	Approved	25.07.2022	Peter	
X.X	±0.25	⑤	Add the order code: AKSPLTx RED	13.01.2014	Winnie			ASSMANN WSW-No. ④ AKSPLTx BLACK ⑤ AKSPLTx RED	
X.XX	±0.20	④	Order code correction	07.01.2014	Winnie			Drawing-No.	
X.XXX	±0.15	③	Update	07.06.2013	Winnie			ASS 0327 CO	rev08
DIM	TOL	Id.	Modification	Date	Name			Customer-No.	SHEET 1 / 1
Angle	TOL								

H

1 2 3 4 5 6 7