

NOTE:

- MATERIAL,
HOUSING: HIGH TEMP PLASTIC, UL94-V0, BLACK
TERMINAL: COPPER ALLOY , SQ=0.40±0.03MM
- FINISH:
TERMINAL: GOLD AT CONTACT,
G/F OVER 1um(40u")MIN Ni OVER ALL
- SPEC.:
PRODUCT SPEC: GS-12-629
PACKING SPEC: GS-14-1420
- THE HSG. WILL WITHSTAND EXPOSURE TO 260C
PEAK TEMP. FOR 10 SEC. IN A WAVE SOLDER APPLICATION
WITH A PCB.
- PRODUCT NUMBERING:
20021611 - 0 0 0 XX X X LF

LEAD FREE


PLATING:
1:GOLD FLASH ALL OVER
4:0.25um(10U")GOLD AT CONTACT
8:0.76um(30U")GOLD AT CONTACT
9:1u" GOLD OVER 30u" PdNi AT CONTACT

PACKING
T: TUBE

PIN COUNT
SEE TABLE 1

TABLE 1

DASH No.	Dim. of Pin	Amount of Pin	Dim.A	Dim.B	Dim.C
-000 06 XX LF	6	2.54	18.31	8.46	
-000 10 XX LF	10	5.08	20.85	11.00	
-000 12 XX LF	12	6.35	22.12	12.27	
-000 14 XX LF	14	7.62	23.39	13.54	
-000 16 XX LF	16	8.89	24.66	14.81	
-000 20 XX LF	20	11.43	27.20	17.35	
-000 26 XX LF	26	15.24	31.01	21.16	
-000 30 XX LF	30	17.78	33.55	23.70	
-000 34 XX LF	34	20.32	36.09	26.24	
-000 40 XX LF	40	24.13	39.90	30.05	
-000 44 XX LF	44	26.67	42.44	32.59	
-000 50 XX LF	50	30.48	46.25	36.40	
-000 60 XX LF	60	36.83	52.60	42.75	
-000 64 XX LF	64	39.37	55.14	45.29	
-000 66 XX LF	66	40.64	56.41	46.56	
-000 68 XX LF	68	41.91	57.68	47.83	



Recommended P.C.B. Layout (2)
Layout Tolerance = ± 0.05 mm

mat'l. code		surface ISO1302 ✓		tolerance ISO1101 ISO406		projection MM		product family MINITEK	
l tre c n n o d r		date		tolerances unless otherwise specified		title			
A	T09-1117	S.LIN	09/15/09	0.X±0.38		1.27X1.27MM BTB EJECT HEADER			
B	T10-0025	S.LIN	01/20/10	0.XX±0.25		VERTICAL TH			
C	BX-N-010365	ZK	01/18/12	0.XXX±0.10		scale 2:1			
		dir		STERLING LIN 09/15/09		dwg no		sheet 1 of 1 size	
		eng		STERLING LIN 09/15/09		20021611		A4	
		chr		GRAY HSIEH 09/15/09		type		Product Customer Drawing	
		appd		JOSEPH 09/15/09					
sheet index	revision	c		sheet		1			