



NOTES:

1. MATERIAL: PVC, SOFT (RMS-55).
2. COLOR: BLUE, TRANSLUCENT.
3. FOR "SPASH PROOF SEAL"
RECOMMENDED WIRE OD=.088 TO .120
(2.2 TO 3.1).

G	FILE NO. WAS ISFPR	SM 10.30.02	TITLE: INSULATING SLEEVE FOR PIN RECEPTACLE				DWG IN		
F	RMS-55 WAS RMS-126	RG 09.26.01			IN (MM)		FINAL		
E	ADDED RMS-126 AND CHANGED FILE NO.	SM 06.26.01	TOLERANCES UNLESS NOTED	FILE # 215010	DWN: P.B.	APP:			
D	DIM .30 (7.6) CHANGED TO REF.	JL 4/12/99	.XX=±.010	MAT'L: SEE NOTES	DT: 03-23-95	DT:	PART #	PRINT TYPE	
C	DIMENSIONS UPDATED	J.L. 8.28.98	.XXX=±.005	RE: RICHCO, INC.	RICHCO INC.		215010	CA	
B	CONV. TO ACAD; COLOR CHANGE-SEE ECN 128	FL 03.23.95	FRAC=±1/64	PO BOX 804238, CHICAGO, 60680					
A	INSIDE DIA. .085 WAS .09	JP 09.12.90	ANG=±1'	(773) 539-4060					
REV	DESCRIPTION	ENGR DATE							