

## 1-Port USB Wall/Travel Charger with Quick Charge 3.0 - Class A 5/9/12V DC Out, 18W

MODEL NUMBER: U280-W01-QC3-1



Travel-sized wall charger with Quick Charge 3.0 USB-A port can charge connected devices up to 4x faster than a standard USB charger.

### Features

**1-Port USB Wall Charger Gets Your Mobile Device up to Capacity Wherever You Are** This single-port USB wall charger with Quick Charge 3.0 technology lets you quickly and safely charge your USB-A mobile device. Plug it into any NEMA 1-15R, NEMA 5-15R or NEMA 5-15/20R AC outlet to ensure your smartphone, tablet, digital camera, e-reader, MP3 player or other USB-A device receives a satisfactory battery charge.

**Charges Quick Charge 3.0-Compatible Devices up to 4 Times Faster than Standard Chargers** The USB-A port supports Quick Charge 3.0 Class A 5/9/12V technology. Instead of charging at a preset power level, the U280-W01-QC3-1 adjusts to provide as much power as your QC 3.0-compliant device's battery can handle. Available outputs include 6–6.5V/3A, 5–9V/2A and 9–12V/1.5A, which can charge your device up to four times faster than traditional USB wall chargers. A multi-colored LED indicates which charge level your connected device is drawing.

**Built-In Auto-Sensing Adjusts to Proper Power Level to Get Your Device to 100%** The USB-A port features auto-sensing technology that detects when a non-Quick Charge device is connected. It then automatically adjusts to the appropriate power level up to 5V/2.4A, perfect for fast-charging tablets and e-readers. The unit protects against overheating, overcurrent and overcharging—in fact, it stops charging as soon as your devices' batteries are at full capacity.

**Folding Plug Design Perfectly Sized for Travel** The compact USB travel charger, small enough to fit in the palm of your hand, is easy to carry in your purse, suitcase, backpack or laptop bag. The NEMA 1-15P plug folds into the unit when not in use to shield it from damage and prevent it from snagging or scratching your bag's contents.

## Specifications

### OVERVIEW

UPC Code

037332239495

### Highlights

- Ideal for charging smartphones, tablets, e-readers and MP3 players while traveling
- Charges Quick Charge 3.0 devices up to 4 times faster than normal USB charging
- Auto-sensing USB port adjusts charging power to your non-QC 3.0 device up to 5V/2.4A
- Stops charging when connected device is at full capacity to protect battery from damage
- Connects to any NEMA 1-15R, 5-15R or 5-15R/20R AC outlet for immediate charging

### Applications

- Charge a smartphone, tablet or other mobile device without taking up a valuable USB port on your computer
- Bring a Quick Charge 3.0 device to capacity up to 4 times faster than with a standard USB wall charger

### Package Includes

- U280-W01-QC3-1 USB Wall/Travel Charger with QC 3.0, 1 USB-A Port, 18W
- Quick Start Guide

Product Type	Wall Charger
Charging Form Factor	Direct Plug-In
Device Compatibility	Phone; Tablet; Amazon Kindle
Technology	USB 2.0 (High Speed)
<b>INPUT</b>	
Nominal Input Voltage(s) Supported	120V AC; 230V AC
Input Connection Type	NEMA 1-15P
Voltage Compatibility (VAC)	100; 100-127; 100-140; 110; 110-240; 120; 125; 127; 200; 200-240
Input Frequency	50 / 60 Hz
Input Plug Type	NEMA 1-15P (NON-POLARIZED)
Input Current	0.45A Max
<b>OUTPUT</b>	
Overload Protection	Yes
<b>BATTERY</b>	
Battery Charging (5V/1.5A Port)	No
<b>POWER</b>	
Power Consumption (Watts)	18
USB Power Delivery (PD) Charging Support	No
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
LED Indicators	Blue (6V-6.5V/3A), Green (5V-9V/2A), Red (9V-12V/1.5A)
<b>CHARGING</b>	
Number of Charging Ports	1
Total Charging Amps	3A
Total Charging Watts	18
Charging Method	USB
Charging Method Detail	Quick Charge 3.0
Charging Port Type	USB A (FEMALE)
Charging Ports	2.4A Quick Charge; USB-A: 2A
Charging Ports Details	3.6V~6.5V/3A, 6.5V~9V/2A, 9V~12V/1.5A
Charging Ports / Amps	3A / 2A / 1.5A
Compatible Devices	Portable Speaker; Smartphone; Tablet

<b>PHYSICAL</b>	
Color	White
Material of Construction	Plastic
Total Number of Ports	1
Shipping Dimensions (hwd / in.)	1.38 x 3.94 x 3.54
Shipping Weight (kg)	0.13
Unit Dimensions (hwd / in.)	2.200 x 1.700 x 1.100
Unit Dimensions (hwd / cm)	5.6 x 4.3 x 2.8
Unit Dimensions (hwd / mm)	56 x 43 x 28
Unit Weight (lbs.)	0.15
Unit Weight (kg)	0.07
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Storage Temperature Range	-4° to 176°F (-20° to 80°C)
Relative Humidity	5% to 90% RH, Non-Condensing
BTUs	0.229
Power Provided to Connected Device(s)	18W
<b>CONNECTIONS</b>	
Number of Ports	1
Side A - Connector 1	NEMA 1-15P (NON-POLARIZED)
Side B - Connector 1	USB A (FEMALE)
<b>INPUT TRANSFORMER</b>	
Input Voltage	Supports an input voltage range of 100-240V
<b>FEATURES &amp; SPECIFICATIONS</b>	
GaN Technology	No
Overcurrent Protection	Yes
Overvoltage Protection	Yes
Over Current Protection	Y
Quick Charge Compliant	3.0
Driver Required	No
<b>STANDARDS &amp; COMPLIANCE</b>	

Product Certifications	UL Listed
Product Compliance	RoHS; REACH; FCC (USA)
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	2-year limited warranty