

Main

Range of Product	Harmony XDA
Product or Component Type	Pre-cabled single axis joystick controller
Device short name	XDA
Type of output signal	Analogue
Bezel material	Chromium plated metal
Additional information	With blank legend plate
Sale per indivisible quantity	1
Mechanical interlocking	With zero position mechanical interlock
[Us] rated supply voltage	12...24 V DC
Current consumption	<= 25 mA at 26 ° 4 mA at zero position
Protection Type	Reverse polarity protection Short-circuit protection on output

Complementary

Mounting diameter	0.87 in (22 mm)
Product Weight	0.37 lb(US) (0.17 kg)
Shape of signaling unit head	Round
Operator profile	Operating shaft
Operator direction information	2 directions
Maximum displacement angle	26 ° +/- 1 °)
Mechanical durability	3000000 cycles
Operating force	10 N 26 ° 3.5 N 3 °
Mounting support	Panel 0.04...0.18 in (1...4.5 mm)
Cable length	1.64 ft (0.5 m)
Wire section	0.00 in ² (0.2 mm ²)

Environment

Protective treatment	TC
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Electrical shock protection class	Class II IEC 60536 Class II NF C 20-030
IP degree of protection	IP65 IEC 60536 IP65 NF C 20-010
Standards	IEC 60337-1 VDE 0660-200 NF C 63-140
Vibration resistance	13 gn 10...500 Hz)IEC 60068-2-6

Ordering and shipping details

Category	22476-JOYSTICKS (NOT CRANE)
Discount Schedule	I
GTIN	3389110350036
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.13 in (5.400 cm)
Package 1 Width	3.39 in (8.600 cm)
Package 1 Length	5.91 in (15.000 cm)
Package 1 Weight	6.74 oz (191.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	12
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	5.60 lb(US) (2.541 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------