



REVISIONS					
P	LTR	DESCRIPTION	DATE	DMN	APVD
C		REVISED PER 003B-0197-05	4/25/05	SS	GS
C1		REVISED PER ECO-09-020689	25AUG09	KK	AEG
C2		REVISED PER ECO-17-005912	22JUL2017	RS	MZ



RECOMMENDED PC BOARD LAYOUT

- △ 0.76um [.000030] MIN GOLD FOR A LENGTH OF 5.08 [.200] MIN FROM MATHING END, 3.81um [.000150] MIN TIN-LEAD FOR A LENGTH OF 2.16 [.085] MIN FROM OPPOSITE END, BOTH OVER 1.27um [.000050] MIN NICKEL ON ENTIRE CONTACT.
- △ 0.76um [.000030] MIN GOLD OVER 1.27um [.000050] MIN NICKEL.
- △ 0.76um [.000030] MIN GOLD FOR A LENGTH OF 5.08 [.200] MIN FROM MATHING END, 3.81um [.000150] MIN TIN FOR A LENGTH OF 2.16 [.085] MIN FROM OPPOSITE END, BOTH OVER 1.27um [.000050] MIN NICKEL ON ENTIRE CONTACT.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

OBSOLETE	△2	△3	POSITIONS 10 AND 21	POSITIONS 18 AND 20	POSITIONS 1 THRU 9, 11 THRU 17,19,22,23	213768-6
OBSOLETE	△2	△3	POSITION 23	NONE	POSITIONS 1 THRU 22	213768-5
	△2	△3	NONE	NONE	ALL POSITIONS	213768-4
OBSOLETE	△2	△1	POSITIONS 10 AND 21	POSITIONS 18 AND 20	POSITIONS 1 THRU 9, 11 THRU 17,19,22,23	213768-3
OBSOLETE	△2	△1	POSITION 23	NONE	POSITIONS 1 THRU 22	213768-2
OBSOLETE	△2	△1	NONE	NONE	ALL POSITIONS	213768-1
			GROUND CONTACT FINISH	SIGNAL CONTACT FINISH	EMPTY CIRCUITS	GROUND CONTACTS
						SIGNAL CONTACTS
						PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN W. LENKER 11/02/92	TE Connectivity
0 PLC ± -	1 PLC ± -	CHK J. McCLINTON 11-16-92	NAME
2 PLC ± ± 0.13 [.005]	3 PLC ± ± -	APVD	PRODUCT SPEC
4 PLC ± ± -	ANGLES ± ± -	FINISH	APPLICATION SPEC
MATERIAL: HOUSING: POLYESTER, UA94V-0 BLACK	CONTACTS: BRASS PER QQ-B-626	SIZE: A1	CAGE CODE: 00779
		WEIGHT: -	DRAWING NO: 213768
		CUSTOMER DRAWING	RESTRICTED TO: -
		SCALE: 2:1	SHEET: 1 OF 1
			REV: C2