

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

## Ozone 3 Click





PID: MIKROE-4654

Ozone 3 Click is a compact add-on board suitable for ozone concentration detection and monitoring. This board features the 110-407, a high-performance ultra-thin electrochemical gas sensor from SPEC Sensors supported by the LMP91000, a high-precision integrated analog frontend IC (AFE) ideal for this sensing application. It provides the reference voltage required by the sensor and offers a choice between the analog output from the AFE IC buffered with the low noise Op-Amp and digital output from the 12-bit SAR A/D converter. This Click board™ represents an ideal choice for health, environmental, industrial, and residential monitoring.

Ozone 3 Click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This <u>Click board™</u> comes as a fully tested product, ready to be used on a system equipped with the mikroBUS™ socket.

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.







MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

## **Specifications**

Туре	Gas,Ozone
Applications	Can be used for ozone concentration detection and monitoring
On-board modules	3SP-O3-20 - high-performance ultra-thin electrochemical gas sensor that can sense ozone concentration up to 20ppm from SPEC Sensors LMP91000 - configurable AFE IC for low-power chemical sensing applications from Texas Instruments
Key Features	Low power consumption, high performance, long life, fast response, high sensitivity, and more.
Interface	Analog,I2C
ClickID	No
Compatibility	mikroBUS
Click board size	L (57.15 x 25.4 mm)
Input Voltage	3.3V or 5V

## Resources

<u>mikroBUS™</u>

**mikroSDK** 

Click board™ Catalog

Click boards™

## **Downloads**

Ozone 3 click 2D and 3D files

**OPA344 datasheet** 

MCP3221 datasheet

LMP91000 datasheet

3SP-O3-20 datasheet

Ozone 3 click example on Libstock





