

# CUC-USB2.0-J1ST-AH/UAF-SMD - USB PCB connectors



1332634

<https://www.phoenixcontact.com/us/products/1332634>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

USB PCB connectors, degree of protection: IP20, number of positions: 4, 480 Mbps, material: Metal, connection method: Solder connection, cable outlet: straight, USB 2.0



## Your advantages

- Optimized for SMD reflow soldering processes
- Data transmission up to 480 Mbps
- Can be processed automatically thanks to tape-on-reel packaging

## Commercial data

Item number	1332634
Packing unit	1 pc
Minimum order quantity	300 pc
Sales key	AB12
Product key	ABNDAA
GTIN	4063151628192
Weight per piece (including packing)	3.167 g
Weight per piece (excluding packing)	3.167 g
Customs tariff number	85366930
Country of origin	CN

# CUC-USB2.0-J1ST-AH/UAF-SMD - USB PCB connectors



1332634

<https://www.phoenixcontact.com/us/products/1332634>

## Technical data

### Product properties

Type	USB-A
Product type	Data connector (device side)
Sensor type	USB 2.0
Number of positions	4
Type of packaging	Tape and Reel
[W] tape width	32.00 mm
[A] coil diameter	330.00 mm
Connection profile	USB-A
Number of slots	1
Type	Socket
Shielded	yes
Cable outlet	straight

### Insulation characteristics

Overvoltage category	I
Degree of pollution	2

### Electrical properties

Rated voltage (III/2)	30 V
Rated surge voltage (III/2)	1500 V
Rated current	1.5 A
Contact resistance	30 mΩ
Frequency range	10 Hz ... 55 Hz
Insulation resistance	1000 MΩ
Transmission medium	Copper
Transmission characteristics (category)	USB 2.0
Transmission speed	480 Mbps
Power transmission	45 W

### Connection data

#### Connection technology

Connection method	Solder connection
-------------------	-------------------

### Dimensions

Width	14.5 mm
Height	7.14 mm
Length	14.13 mm
Orientation to	90.00 °

### Material specifications

Color of the housing part	black
---------------------------	-------

# CUC-USB2.0-J1ST-AH/UAF-SMD - USB PCB connectors



1332634

<https://www.phoenixcontact.com/us/products/1332634>

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Gold over nickel
Contact carrier material	LCP
Housing material	Metal

## Cable/line

Test voltage Core/Core	500 V
Test voltage Core/Shield	500 V
Acceleration	3.1 m/s <sup>2</sup>
Halogen-free	yes

## Mechanical properties

### Mechanical data

Insertion/withdrawal cycles	> 1500
Insertion force per signal contact	35.00 N
Extraction force per signal contact	< 10 N

## Environmental and real-life conditions

### Test specification

Specification	EIA 364-1000
Frequency	10-55 Hz
Sweep speed	1 octave/min
Amplitude	1.52 mm
Test duration	2 h
Contact resistance R <sub>1</sub>	30 mΩ

### Test specification

Specification	60068-2-27
Acceleration	50 g
Number of shocks per direction	18

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-55 °C ... 85 °C

## Mounting

Mounting type	SMD soldering
Connection method	Solder connection

### Processing notes

Process	SMD
Moisture Sensitive Level	MSL 1
Classification temperature T <sub>c</sub>	260 °C
Solder cycles in the reflow	3

# CUC-USB2.0-J1ST-AH/UAF-SMD - USB PCB connectors



1332634

<https://www.phoenixcontact.com/us/products/1332634>

## Classifications

### ECLASS

ECLASS-11.0	27440390
ECLASS-12.0	27440390
ECLASS-13.0	27440390

### ETIM

ETIM 8.0	EC001121
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# CUC-USB2.0-J1ST-AH/UAF-SMD - USB PCB connectors



1332634

<https://www.phoenixcontact.com/us/products/1332634>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)