

## Dual 4-Input OR/NOR Gate

### ELECTRICAL CHARACTERISTICS


Characteristic	Symbol	-30°C		+25°C		+85°C		Unit
		Min	Max	Min	Max	Min	Max	
Power Supply Drain Current	$I_E$	—	—	—	28	—	—	mAdc
Input Current	$I_{inH}$	—	—	—	350	—	—	$\mu$ Adc
Switching Times								ns
Propagation Delay	$t_{+-}$	0.6	1.8	0.6	1.7	0.6	1.9	
	$t^{-+}$	0.6	1.6	0.6	1.5	0.6	1.7	
Rise Time, Fall Time (10% to 90%)	$t^+, t^-$	0.6	2.2	0.6	2.1	0.6	2.3	ns

**MC1660**



L SUFFIX  
CERAMIC PACKAGE  
CASE 620-10

### LOGIC DIAGRAM



$$OUT = IN1 + IN2 + IN3 + IN4$$

$$\overline{OUT} = \overline{IN1 + IN2 + IN3 + IN4}$$

$$V_{CC1} = PIN 1$$

$$V_{CC2} = PIN 16$$

$$V_{EE} = PIN 8$$


$$t_{pd} = 0.9 \text{ ns typ (510 ohm load)}$$

$$= 1.1 \text{ ns typ (50 ohm load)}$$

$$P_D = 120 \text{ mW typ/pkg (No load)}$$

$$\text{Full Load Current, } I_L = -25 \text{ mAdc max}$$

### PIN ASSIGNMENT



**4**

