Mallory Sonalert Products, Inc.				JT120-Y-CEL		
Sales Outline Drawing				Revision: C		
Specifications:						
Stack Number:	1 4	T				
LED Color:	YELLOW					
Connection Wires:	Yellow and Brown					
LED Current Draw:	<230 mA					
Rated Voltage:	\250 IIIA		120 VAC		1	
Operating Voltage:			90-120 VAC			
Sound Level Category:	Loud	Loud	Loud		Loud	
Mode of Operation:	Continuous	Medium Pulse (5PPS)	Double Pulse (0.5PPS)	Continuous	Continuous for 5 sec then 0.1s beep until	
Connection:	Black and Gray Wires	Black and Gray Wires; Orange wire connected to	Black and Gray Wires; Pur wire connected to Green/Ye wire	low black and t	Black and Gray wires: Orange and Purple	
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max.		40mA Max.	
Loudness @ 1m:		1	80-85 dB(A) Typ.			
Frequency:	2000 ± 500 Hz					
Total Max Current:	<270mA with all LED's and sound unit working					
Operating Temperature:	-25° ~ +60°C					
Lens Color:	Opaque White					
Material:	ABS FR15U					
Mounting Method:	Stainless Steel Pole - Black					
Weight Typical (g):	645					
NEMA 12:	Approved					
Options:			Please contact factory.			
3.7 [94.1] YELLUW		5.6 [422.0]————	Ø0.20 [Ø5.2] 3 places #10 or 5mm screws for mounting	Ø0.57 [Ø14. for wire:	5	
LED OPERATION: CONNEC	_		0.95 [24.3] MOUNT DIAGE	АМ	31	
SOUND OPERATION: CONNECT GRAY AND BLACK WIRES TO POWER FOR CONTINUOUS SOUND. FOR MEDIUM PULSE, CONNECT GRAY & BLACK TO POWER AND ORANGE WIRE TO GREEN/YELLOW WIRE.						
			BLACK TO POWER AND PU			
			CK TO POWER AND ORANG			