






APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/16/18	



RECOMMENDED PCB LAYOUT



Model No.	ASJ-200-B-HT	ASJ-200-C-HT	ASJ-200-D-HT
Schematic			

SPECIFICATIONS:

Material:
Housing: Hi-Temp Thermoplastic, reated UL94V-0, Color: Black
Contacts: Copper Alloy
Plating:
Silver over Copper underplate overall
Electrical:
Rating: 30VDC, 0.5A
Contact Resistance: 30 mohm max.
Insulation Resistane: 100 Mohm min. @ 500 VDC
Dielectric withstanding voltage: 500 VAC
Temperature Rating:
Operating temperature: -20°C to +70°C
Environmental:
Lead free, RoHS compliant.



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE MILLIMETERS TOLERANCES: EXCEPT AS NOTED		
MM	ANGLE	
.X ± 0.50	X ± 5°	
.XX ± 0.30	.X ± 3°	
.XXX ± 0.15	.XX ± 2°	
APPROVALS		DATE
DRAWN	HR	11/16/18
CHECKED	AC1	11/16/18
APPROVED		

ADAM TECH
INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE 3.5MM STEREO PHONE JACK, RIGHT ANGLE		
SIZE X	PART NO. ASJ-200-X-HT	REV. -
REF: S00002C	SCALE: NTS	SHEET 1 OF 1