Technical Data/ Product Specifications

3

Safety-WalkTM

Wet Area Matting 1500

(Also known as 3MTM NomadTM Medium Traffic Unbacked Matting)

1.0 ProductDescription

The product is an unbacked, nonwoven, open and porous matting made from continuous vinyl filaments. Overall, the mat provides antifatigue

comfort while collecting dirt and draining water.

2.0 Intended Use For use as a comfort cushion for bare feet while allowing water to drain

through the matting. 3M Safety-Walk Wet Area Matting 1500 also can be used as a fatigue reducing cushion mat. Applications include locker rooms, shower areas, and around saunas. Not recommended in kitchens

or greasy, oily areas.

3.0 Standard Sizes Rolls: 3 ft. x 20 ft.

Custom Lengths:

Width: 3 feet

Length: 2 feet to 40 feet in 1 foot increments

4.0 Color Blueberry, Spruce

5.0 Requirements General Requirements

The product shall be made of oil-resistant, all-vinyl, nonwoven

continuous filaments bonded together to form a durable, resilient, water-

resistant matting.

Detailed Requirements:

Weight (minimum)

ASTM D418-68 3.3 lbs./yd. 2 (1.8 kg/m 2)

Thickness (minimum) [1] 0.41 inches (10.3 mm)

ASTM D418-68

Microbiological Properties Inhibiting to fungal growth

ASTM G-21-90

Flammability

DOC-FF-1-70 (Pill Test) Passes

5.0 Requirements (continued)

Chemical Resistance[2]

Water Excellent [3] 1% Soap Excellent 50% Ethyl Alcohol Good Hydrocarbon Solvents [4] Poor Chlorinated Hydrocarbon Solvents [5] Poor Gasoline Poor Cooking Oil [6] Poor 5% Acetic Acid Excellent 5% Sodium Hydroxide Excellent

- [1] Product may be compressed in package. Thickness is manufactured loft before packaging.
- [2] All tests 7 days @ 72° F, unless otherwise noted.
- [3] Excellent Slight effect on product, less than 1% weight loss.

Good – Product stiffens or discolors slightly, less than 3% weight loss.

Poor – Product becomes unsuitable for use. $3M^{TM}$ Safety-WalkTM Matting 1500 should not be used where it will regularly contact these chemicals.

- [4] Mineral Spirits.
- [5] Methylene Chloride, Perchloroethylene, Chloroform.
- [6] Peanut Oil.

6.0 Packaging and Marking

Packaging: One per carton.

Marking: Each carton shall be marked with product name, size, color, and manufacturer's trade name.

7.0 Cleaning

Routine Maintenance:

For Dry Areas:

- 1. Shake dirt from mat and remove from service area.
- 2. Sweep and remove dirt from service area.
- 3. If needed, mop or flush service area.
- 4. If needed, flush both sides of the mat with warm water to remove remaining dirt.
- 5. Allow mat to dry flat before placing mat back into service.

For Wet Areas:

Flush both sides of mat daily with warm water.

Periodic Maintenance:

- 1. Remove mat from service area if needed (no drainage in area).
- 2. Mop mat(s) on both sides with a disinfectant cleaner and let stand for ten (10) minutes.
- 3. Flush mat with warm water.
- 4. Allow mat to dry flat before placing back into service.

8.0 Weight and Cube per Case

Size	Approximate	Cube
	Weight	

3 ft. x 20 ft. 27 lb. 3.5 cu. ft.

3M Branch Sales Offices

ANCHORAGE

11151 Calaska Circle Anchorage, AK 99515 Telephone: 907/522-5200 Facsimile: 907/522-1645

CONTINENTAL UNITED STATES

Customer Service Department 3M Center Building 223-5N-07 St. Paul, MN 55144-1000 Order Entry 1-800-852-9722 Facsimile: 1-800-447-0408

HONOLULU

4443 Malaai Street Honolulu, HI 96818 Mail to: P.O. Box 30048 Honolulu, HI 96820 Telephone: 808/422-2721 Facsimile: 808/422-9557

3M CANADA

1840 Oxford Street East London, Ontario, Canada N5V 3G2

Mail to: P.O. Box 5757 London, Ontario, Canada

N6A 4T1

Telephone: 800/364-3577 Facsimile: 800/479-4453

Important Notice:

This flyer is intended to be an introductory summary. The information provided is based upon typical conditions and is believed to be reliable; however, due to the wide variety of intervening factors 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.