

System 230 Binocular Microscopes

Full-Featured Economical Microscopes for Light-Duty Applications

LX Microscopes by UNITRON's System 230 is a full-featured binocular microscope system with a sealed polymer body. It is the perfect solution for economically-budgeted production applications. Designed and intended for lighter duty usage in assembly, rework, and limited inspection processes. Featuring a 20mm field of view, it fits many applications where higher magnification isn't required.







P/N 20784

TECHNICAL DESCRIPTION

OPTICS:

20mm field of view, 10X widefield eyepieces with individual diopter adjustment and eyeshields. 97mm working distance (with included 1.0X lens), 180mm (over 7'') when used with an optional 0.5X reducing lens.

MAGNIFICATION:

Standard 7X - 30X magnification range.

LENSES:

High-quality achromatic lenses with anti-reflective coatings.

ERGONOMICS:

Standard 45° viewing angle.



ZOOM:

0.7X – 3X zoom range (4.3:1 zoom ratio) controlled by dual graduated knobs located on both sides of the head.

CONSTRUCTION:

Sealed Polymer body.

MOUNTING

Dual boom ball bearing stand with 15'' vertical post and 22.5'' horizontal ($11.1'' \times 10.25''$ base), Single boom stand with 20'' vertical post and 22'' horizontal ($15'' \times 10''$ base), Non-Illuminated plain stand with 12.5'' vertical track and 3.9'' focus travel.

Additional lighting options sold separately.

5-YEAR WARRANTY. Visit our website for full details.

BALL BEARING BOOM STANDS



SINGLE BOOM STANDS



NON-ILLUMINATED PLAIN STANDS





Working Distance (mm)



P/N 20784

180

| SYSTEM 230 OPTICAL DATA | | | | | |
|-------------------------|-----------------------------|-----------------|------------|---------------|--|
| | | Objective | | | |
| Eyepieces | | 1.0X (included) | 0.5X | 0.75X | |
| | Total Magnification (Range) | 7X - 30X | 3.5X - 15X | 5.25X - 22.5X | |
| 1 OX | Field of View Diameter (mm) | 25.7 - 6 | 51.4 - 12 | 34.3 - 8 | |

97

| PRODUCT TABLE Part number | Microscope | Description | | |
|---------------------------|----------------------|--|--|--|
| 20714* | System 230 | S-Z 20mm Binocular, Single Boom | | |
| 20716* | System 230-LEDQRL | S-Z 20mm Binocular, Single Boom, Quadrant LED Light | | |
| 20717* | System 230-LEDECO | S-Z 20mm Binocular, Single Boom, LED-ECO Ring Light | | |
| 20780* | System 230-LED3000 | S-Z 20mm Binocular, Single Boom, LED-3000 Ring Light | | |
| 20714BB* | System 230BB | S-Z 20mm Binocular, BB Stand | | |
| 20716BB* | System 230BB-LEDQRL | S-Z 20mm Binocular, BB Stand, Quadrant LED Ring Light | | |
| 2071 <i>7</i> BB* | System 230BB-LEDECO | S-Z 20mm Binocular, BB Stand, LED-ECO Ring Light | | |
| 20780BB* | System 230BB-LED3000 | S-Z 20mm Binocular, BB Stand, LED-3000 Ring Light | | |
| 20783 | System 230PFS-LEDECO | S-Z 20mm Binocular, Non-Illuminated Plain Stand, LED-ECO Ring Light | | |
| 20784 | System 230PFS | S-Z 20mm Binocular, Non-Illuminated Plain Stand | | |
| 20736 | - | 0.75X Reducing Lens (For System 230 models only) | | |
| 20750 | _ | O.5X Reducing Lens (For System 230 models only) 5 YEAR WARRANTY 9001 • 14001 | | |

120