

Ratings

Voltage: 300 V
 Temperature: 105 °C
 Flammability: VW-1



Conductor

Conductor count: 2
 Gauge: 14 AWG 2.08 mm²
 Material: bare copper strands
 Strand size: Ø 0.254 mm x 41
 Maximum resistance at 20 °C: 8.62 ohms/km

Outer jacket

Material: XLPE, LSZH (low smoke zero halogen)
 Color: red and black
 Diameter: 6 ±0.20 mm (3 ±0.15 x 2)
 Nominal thickness: 0.53 mm
 Resistance at 20 °C: 100 MΩ /km min

Wire marking: E339579 UL AWM STYLE 4384 14 AWG 105°C
 300V VW-1 TENSILITY



Revision:	Date:	Description:	Prepared: PB <small>Digitally signed by PB Date: 2022.09.05 08:18:17 -07'00'</small>	Notes:	TENSILITY <small>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</small>	
A	9/1/2022	Initial release	Verified: JD <small>Digitally signed by JD Date: 2022.09.08 09:10:55 -07'00'</small>	RoHS compliant		
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Function test: no open, no short circuit, no intermittent	Size: Part number:	
				Description:	A	30-02854
				Wire, 2C, 14 AWG, UL4384, 300V, 105C, 6.0 mm, VW-1, LSZH, XLPE, red and black	Scale: 10:1	Sheet 1 of 1

5

4

3

2

1