

RC-07S1N121L00 - 1594574

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable connector, with Pg13.5 connection thread, straight, shielded: No, Screw locking, M23, Number of positions: 7, Type of contact: Socket, Solder connection, Cable diameter: 9 mm ... 13 mm

The figure shows the 12-pos. product version, with standard DIN cable gland



Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	87.410 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Product type	Circular connector (cable-side)
Approval	EAC
Cable diameter	9 mm ... 13 mm
Coding	N
Type	Cable connector, with Pg13.5 connection thread
Number of positions	7
Thread	M23
Rated voltage (IEC)	300
Rated current (IEC)	20
Knurl material	Metal
Shielding	No
Signal type	Signal


RC-07S1N121L00 - 1594574

Technical data


Connection method	Solder connection
-------------------	-------------------

Drawings

Schematic diagram



Dimensional drawing



Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	27440102
eCl@ss 9.0	27440103

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC001121

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

RC-07S1N121L00 - 1594574

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC B.01742
