

Mini vibration motor SMD

SKU: 316040005



(images/product/316040005 1_02.jpg)

Operating condition

Item	Specification	Condition remark
2-1 Rated voltage	1.3VDC	
2-2 Operating voltage	0.9~1.6VDC	
2-3 Rated load	Vibraton weight	As soecufued in outline drawing
2-4 Rated speed	9000±1500rpm	
2-5 Rotation	CW (clockwize)	
2-6 Motor Position	All position	
2-7 Operating environment	-20~60°C	
	10~90%Rh	
2-8 Storage environment	-40~80°C	No condensation of moisture
	5~95%Eh	

Measuremen codition

Item	Specification	Condition remark
3-1 Temperature	20±2°C	
3-2 Humidity	65±5%RH	
3-3 Motor position	Moror shaft horizontal	Lock the motor in a test fixture

All date are based on the measurement under the temperature of 20°C and humidity65% andRH.hower.the langes of temperature5~35°C and humiddity45~85%RH are to be applicable as long as long as no problems.

Overview

(<http://www.seeedstudio.com/depot/Shenzhen-2U-t-11.html?ref=pinfo>)

(<http://www.seeedstudio.com/depot/Others-m-24.html?ref=pinfo>)

Weight: 3 g

Designer: Others
Other Products From
This Designer